

PDF technical sheet 33022A



Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	4.3307 "
D	6.6929 "
B	1.8504 "
C	1.4567 "
T	1.8504 "
a	1.2992 "
rs min	0.0984 "
r1s min	0.0787 "
e	0.29
Y2	2.09
Y0	1.15
Mass	14.67 oz
ISO 355 reference	T2DE110
Brand	SNR



Product performance	
Dynamic load, C	295 kN
Rating life coefficient, A2	1
Static load, C0	520 kN
Fatigue limit load, Cu	57.40 kN
Nref	2,700 RPM
Nlim	4,000 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C



Abutment dimensions

da max	4.7638 "
db min	4.8031 "
Da min	5.9843 "
Da max	6.2992 "
Db min	6.3386 "
Ca min	0.2756 "
Cb min	0.3937 "
ra max	0.0787 "
r1a max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_o = X_o.F_r + Y_o.F_a$$

X_o	Y_o
0.5	Y0

If $P_o \leq F_r$, then use $P_o = F_r$

The values for e, Y2 and Y0 are shown in the above table