

PDF technical sheet 33217A



Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Product definition	
d	3.3465 "
D	5.9055 "
B	1.9291 "
C	1.4567 "
T	1.9291 "
a	1.4646 "
rs min	0.0984 "
r1s min	0.0787 "
e	0.42
Y2	1.43
Y0	0.79
Mass	12.63 oz
ISO 355 reference	T3EE085
Brand	SNR



Product performance	
Dynamic load, C	295 kN
Rating life coefficient, A2	1
Static load, C0	435 kN
Fatigue limit load, Cu	50.60 kN
Nref	3,000 RPM
Nlim	4,600 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C



Abutment dimensions

da max	3.7402 "
db min	3.8189 "
Da min	5.0394 "
Da max	5.5118 "
Db min	5.6693 "
Ca min	0.2756 "
Cb min	0.4724 "
ra max	0.0787 "
r1a max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 \leq F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table