


Werkstoff 1.4401

Betriebsdruck:
Betriebstemperatur:

max. 12 bar
-10 °C bis +400 °C



562-2 ES



Art.-Nr.	A	C	D	SW
562-0 ES	M 5	3,5	16	8
562-1 ES	G 1/8	6,0	25	13
562-2 ES	G 1/4	8,0	33	16
562-3 ES	G 3/8	9,0	40	19
562-4 ES	G 1/2	10,0	47	24

Art.-Nr.	Gewinde	1 BAR	2 BAR	3 BAR	4 BAR	5 BAR	6 BAR	mit Schalldämpfer in DB
562-0 ES	M 5	53	64	72	77	81	85	
562-1 ES	G 1/8	59	68	75	81	85	90	
562-2 ES	G 1/4	65	76	81	86	89	93	
562-3 ES	G 3/8	70	78	86	91	96	101	
562-4 ES	G 1/2	73	80	85	89	92	95	

Art.-Nr.	Gewinde	1 BAR	2 BAR	3 BAR	4 BAR	5 BAR	6 BAR	Durchfluss in Nm ³ /h
562-0 ES	M 5	3,3	4,5	5,5	6,3	7,0	7,5	
562-1 ES	G 1/8	11,0	15,0	18,0	21,0	24,0	28,0	
562-2 ES	G 1/4	19,0	30,0	36,0	41,0	46,0	51,0	
562-3 ES	G 3/8	34,0	46,0	56,0	65,0	73,0	78,0	
562-4 ES	G 1/2	54,0	71,0	85,0	97,0	107,0	115,0	

Art.-Nr.	Gewinde	1 BAR	2 BAR	3 BAR	4 BAR	5 BAR	6 BAR	ohne Schalldämpfer in DB
562-0 ES	M 5	84	92	98	110,0	114,0	112,0	
562-1 ES	G 1/8	101	110	118	122,0	122,5	122,6	
562-2 ES	G 1/4	109	112	124	124,0	124,0	124,0	
562-3 ES	G 3/8	107	116	124	124,2	125,0	125,0	
562-4 ES	G 1/2	110	118	120	120,0	123,0	124,0	

Art.-Nr.	Gewinde	1 BAR	2 BAR	3 BAR	4 BAR	5 BAR	6 BAR	Geräuschdämpfung Diff.
562-0 ES	M 5	31	28	26	33,0	33,0	27,0	
562-1 ES	G 1/8	42	42	43	41,0	37,5	32,6	
562-2 ES	G 1/4	44	36	43	38,0	35,0	31,0	
562-3 ES	G 3/8	37	38	38	33,2	29,0	24,0	
562-4 ES	G 1/2	37	38	35	31,0	31,0	29,0	

