

Betriebstemperatur:

Druckbereich:

Innengewinde:


Außengewinde:

-20 °C bis +150 °C

max. 150 bar

zylindrisch nach DIN EN ISO 228-1


konisch nach ISO 7-1



ES 253.01

Winkelstück, außen/außen, Edelstahl


Artikel-Nr.	D1	D2	L1	L2
ES 253.00	R 1/8	R 1/8	17,0	17,0
ES 253.01	R 1/4	R 1/4	21,0	21,0
ES 253.02	R 3/8	R 3/8	24,0	24,0
ES 253.03	R 1/2	R 1/2	30,0	30,0



ES 253.12

Winkelstück, innen/innen, Edelstahl


Artikel-Nr.	D1	L1
ES 253.11	G 1/8	19,0
ES 253.12	G 1/4	23,0
ES 253.13	G 3/8	25,5
ES 253.14	G 1/2	32,0



ES 253.15

Winkelstück, außen/innen, Edelstahl


Artikel-Nr.	D1	D2	L1	L2
ES 253.15	R 1/8	G 1/8	18,0	19,0
ES 253.16	R 1/4	G 1/4	25,0	23,0
ES 253.17	R 3/8	G 3/8	24,0	25,5
ES 253.18	R 1/2	G 1/2	30,0	32,0



ES 254.34

T-Stück, innen/innen/innen, Edelstahl

Artikel-Nr.	D1	L1	L2
ES 254.33	G 1/8	19,0	38,0
ES 254.34	G 1/4	23,0	46,0
ES 254.35	G 3/8	25,5	51,0
ES 254.39	G 1/2	32,0	64,0



ES 254.42

T-Stück, innen/außen/innen, Edelstahl

Artikel-Nr.	D1	D2	L1	L2
ES 254.41	R 1/8	G 1/8	18,0	38,0
ES 254.42	R 1/4	G 1/4	25,5	46,0
ES 254.43	R 3/8	G 3/8	24,0	51,0
ES 254.44	R 1/2	G 1/2	30,0	64,0