



Betriebsdruck:
 Betriebstemperatur:
 Innengewinde:
 Außengewinde


max. 20 bar
 max. 175 °C
 Rp-Gewinde nach ISO 7-1
 R-Gewinde nach ISO 7-1



253.13-ES

Winkelstück 90°, innen/innen, Rp-Gewinde nach ISO 7-1


Artikel-Nr.	Gewinde	A	B
253.11-ES	1/8	16,4	16,4
253.12-ES	1/4	19,2	20,0
253.13-ES	3/8	22,5	23,5
253.21-ES	1/2	27,4	27,4
253.22-ES	3/4	31,1	32,2
253.23-ES	1	36,9	40,0



253.46-ES

Winkelstück 45°, innen/innen, Rp-Gewinde nach ISO 7-1



Artikel-Nr.	Gewinde	L	Ø
253.41-ES	1/8	15,6	16,5
253.42-ES	1/4	15,9	19,9
253.43-ES	3/8	17,6	23,5
253.44-ES	1/2	19,2	27,6
253.45-ES	3/4	22,8	32,5
253.46-ES	1	26,7	40,0



253.18-ES

Winkelstück 90°, innen/außen, IG: Rp-Gewinde nach ISO 7-1, AG: R-Gewinde nach ISO 7-1



Artikel-Nr.	Gewinde	H	L
253.15-ES	1/8	17,2	24,1
253.16-ES	1/4	19,9	28,3
253.17-ES	3/8	22,0	32,6
253.18-ES	1/2	27,1	38,0
253.19-ES	3/4	32,3	44,4
253.20-ES	1	37,5	51,6



253.66-ES

Kreuzverteiler, 4 x innen, Rp-Gewinde nach ISO 7-1

Artikel-Nr.	Gewinde	A
253.61-ES	1/8	19,0
253.62-ES	1/4	19,0
253.63-ES	3/8	23,1
253.64-ES	1/2	26,8
253.65-ES	3/4	31,7
253.66-ES	1	37,9



254.36-ES

T-Verteiler, 3 x innen, Rp-Gewinde nach ISO 7-1

Art.-Nr.	Gewinde	L	A
254.33-ES	1/8	34,0	16,7
254.34-ES	1/4	37,7	19,0
254.35-ES	3/8	46,1	21,8
254.36-ES	1/2	54,0	26,8
254.37-ES	3/4	62,2	31,2
254.38-ES	1	72,5	36,0