

Schalldämpfer aus Sinterbronze, flache Ausführung, mit Innengewinde


Zur Reduzierung von Abluftgeräuschen an pneumatischen Anlagen.

Betriebsdruck:
Betriebstemperatur:

max. 12,0 bar
-10 °C bis + 150 °C



565-1



Art.-Nr.	A	ØB	C	D	SW
565-0	M 5	3,5	7,5	4,0	-
565-1	G 1/8	11,0	10,5	6,0	13
565-2	G 1/4	14,0	11,0	6,0	16
565-3	G 3/8	17,0	12,0	7,5	19
565-4	G 1/2	22,0	13,0	8,0	24

Art.-Nr.	Gewinde	1 BAR	2 BAR	3 BAR	4 BAR	5 BAR	6 BAR	mit Schalldämpfer in DB
565-0	M 5							
565-1	G 1/8	68,0	80,0	87,0	88,0	89,0	90,0	
565-2	G 1/4	68,0	76,0	82,0	85,0	88,0	90,0	
565-3	G 3/8	80,0	84,0	89,0	92,0	95,0	97,0	
565-4	G 1/2	83,0	91,0	97,0	100,0	102,0	105,0	

Art.-Nr.	Gewinde	1 BAR	2 BAR	3 BAR	4 BAR	5 BAR	6 BAR	Durchfluss in Nm/h
565-0	M 5							
565-1	G 1/8	3,4	5,0	6,0	6,5	7,3	8,0	
565-2	G 1/4	6,4	9,0	10,7	12,3	13,8	15,0	
565-3	G 3/8	10,5	14,3	16,7	18,0	20,0	22,0	
565-4	G 1/2	15,5	20,0	25,0	28,0	30,0	36,0	

Art.-Nr.	Gewinde	1 BAR	2 BAR	3 BAR	4 BAR	5 BAR	6 BAR	ohne Schalldämpfer in DB
565-0	M 5	84,0	92,0	98,0	110,0	114,0	112,0	
565-1	G 1/8	101,0	110,0	118,0	122,0	122,5	122,6	
565-2	G 1/4	109,0	112,0	124,0	124,0	124,0	124,0	
565-3	G 3/8	107,0	116,0	124,0	124,2	125,0	125,0	
565-4	G 1/2	110,0	118,0	120,0	120,0	123,0	124,0	

Art.-Nr.	Gewinde	1 BAR	2 BAR	3 BAR	4 BAR	5 BAR	6 BAR	Geräuschdämpfung Diff.
565-0	M 5							
565-1	G 1/8	33,0	30,0	31,0	34,0	33,5	32,6	
565-2	G 1/4	41,0	36,0	42,0	39,0	36,0	34,0	
565-3	G 3/8	27,0	32,0	25,0	32,2	30,0	28,0	
565-4	G 1/2	27,0	27,0	23,0	20,0	21,0	19,0	

