



- aus Kunststoff (POM) blau -

Betriebsdruck: 0 – 10,0 bar  
Temperaturbereich: -10 °C bis +60 °C





13.765

**Winkelverschraubung**, starr, Außengewinde konisch, Gewinde nach ISO 7-1



| Art.-Nr. | Gewinde | für Schlauch | NW mm | B    | L    | L <sub>1</sub> | H    | H <sub>1</sub> | H <sub>2</sub> |
|----------|---------|--------------|-------|------|------|----------------|------|----------------|----------------|
| 13.760   | R 1/8   | 6/4          | 3     | 11,0 | 29,0 | 23,0           | 22,0 | 16,0           | 8,0            |
| 13.761   | R 1/8   | 8/6          | 5     | 14,0 | 29,0 | 23,0           | 24,0 | 17,0           | 8,0            |
| 13.765   | R 1/4   | 6/4          | 3     | 14,0 | 32,0 | 24,0           | 25,0 | 19,0           | 11,0           |
| 13.766   | R 1/4   | 8/6          | 5     | 14,0 | 33,0 | 25,0           | 27,0 | 20,0           | 11,0           |
| 13.768   | R 1/4   | 12/9         | 7     | 17,0 | 36,0 | 28,0           | 33,0 | 23,0           | 13,0           |
| 13.774   | R 3/8   | 12/9         | 7     | 17,0 | 36,0 | 28,0           | 33,0 | 23,0           | 13,0           |



| Art.-Nr.       | für Schlauch | Gewinde | SW | D    | L    | L <sub>1</sub> | L <sub>2</sub> |
|----------------|--------------|---------|----|------|------|----------------|----------------|
| 13.760, 13.765 | 6/4          | M 10x1  | 12 | 6,2  | 13,0 | 10,5           | 5,0            |
| 13.761, 13.766 | 8/6          | M 12x1  | 14 | 8,2  | 13,0 | 10,5           | 5,0            |
| 13.768, 13.774 | 12/9         | M 16x1  | 19 | 12,4 | 14,0 | 11,5           | 6,0            |