according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version	Revision Date:	Date of last issue: 08.09.2021	Print Date:
3.2	20.01.2023	Date of first issue: 26.10.2016	19.05.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Product name	: OKS 235	51
1.2 Relevant identified uses of	the substance	or mixture and uses advised against
Use of the Sub- stance/Mixture	: Lubrican	t spray
Recommended restrictions on use	: Restricte	d to professional users.
1.3 Details of the supplier of th	e safety data s	sheet
Company	: OKS Spe Ganghof D-82216 Tel.: +49 Fax.: +49	ezialschmierstoffe GmbH
E-mail address of person responsible for the SDS		ks-germany.com Compliance Management
National contact	:	
1.4 Emergency telephone num Emergency telephone num- ber		2 3051 517
SECTION 2: Hazards identifi	cation	
2.1 Classification of the substa	nce or mixture	9
Classification (REGULATIO	ON (EC) No 12	72/2008)
Aerosols, Category 1		H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2		H315: Causes skin irritation.
Specific target organ toxicity posure, Category 3, Central system	•	H336: May cause drowsiness or dizziness.



H304: May be fatal if swallowed and enters air-

Aspiration hazard, Category 1

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

UNS 233	D [*] I			
Version 3.2	Revision Date: 20.01.2023		st issue: 08.09.2021 st issue: 26.10.2016	Print Date: 19.05.2025
			ways.	
Long- egory	term (chronic) aquat 3	ic hazard, Ca	 H412: Harmful to aqua fects. 	atic life with long lasting ef-
2.2 Label	elements			
	I ling (REGULATION rd pictograms	(EC) No 127	2/2008)	>
Signa	l word	: Dang	er	
Hazaı	Hazard statements :		Pressurised co	nmable aerosol. ontainer: May burst if heated. swallowed and enters air- ritation
		H315 H336 H412	May cause dro	owsiness or dizziness. atic life with long lasting ef-
Preca	utionary statements	· Preve	ntion:	
		P210		m heat, hot surfaces, sparks, nd other ignition sources. No
		P211		on an open flame or other
		P251		or burn, even after use.
		Resp	onse:	
		P301	+ P310 IF SWALLOW POISON CEN	ED: Immediately call a TER/ doctor.
		P331	Do NOT induc	e vomiting.
		Stora	-	
		P410		unlight. Do not expose to exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative tive and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version	Revision Date:	Date of last issue: 08.09.2021	Print Date:
3.2	20.01.2023	Date of first issue: 26.10.2016	19.05.2025

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature

: Active agent with propellant and solvent.

Components

Components				1
Chemical name	CAS-No.	Classification	specific concen-	Concentration
	EC-No.		tration limit	(% w/w)
			M-Factor	
	Index-No.		Notes	
	Registration number		Acute toxicity	
			estimate	
Hydrocarbons, C6-C7,		Flam. Liq.2; H225		>= 10 - < 20
n-alkanes, isoalkanes,	921-024-6	Skin Irrit.2; H315		
cyclics, <5% n-hexane		STOT SE3; H336		
		Asp. Tox.1; H304		
	01-2119475514-35-	Aquatic Chronic2;		
	XXXX	H411		
Kaolin, calcined	92704-41-1	Eye Irrit.2; H319		>= 1 - < 10
Raolin, calcined	296-473-8	STOT SE3; H335;		>= 1 - < 10
	290-475-8	EUH066		
Substances with a work	place exposure limit :			
butane	106-97-8	Flam. Gas1A;		>= 30 - < 50
	203-448-7	H220		
		Press. GasCompr.	Note U (table	
	601-004-00-0	Gas; H280	3.1), Note C	
	01-2119474691-32-			
	XXXX			
propane	74-98-6	Flam. Gas1A;		>= 10 - < 20
	200-827-9	H220		
		Press. GasCompr.	Note U (table	
	601-003-00-5	Gas; H280	3.1)	
	01-2119486944-21-			
	XXXX			
distillates (petroleum),	64742-54-7	Not classified		>= 10 - < 20
alounated (petroleum),				2 10 120



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version 3.2	Revision Da 20.01.2023		ssue: 08.09.2021 issue: 26.10.2016	Print I 19.05	Date: .2025
hydrotreated heavy paraffinic		265-157-1 649-467-00-8 01-2119484627-25- XXXX		Note L	
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified		265-169-7	Not classified	Note L	>= 10 - < 20
(stabilised) 231-072-3 013-002-0		7429-90-5 231-072-3 013-002-00-1 01-2119529243-45- XXXX	Flam. Sol.1; H228	Note T	>= 1 - < 10
isobutane	9	75-28-5 200-857-2 601-004-00-0 01-2119485395-27- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled	 Call a physician or poison control centre immediately. Remove person to fresh air. If signs/symptoms continue, get medical attention. Keep patient warm and at rest. If unconscious, place in recovery position and seek medical advice. Keep respiratory tract clear. If breathing is irregular or stopped, administer artificial respira- tion.
In case of skin contact	 Take off all contaminated clothing immediately. Get medical attention immediately if irritation develops and persists. Wash clothing before reuse. Thoroughly clean shoes before reuse. Wash off immediately with plenty of water.
In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids,



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version 3.2	Revision Date: 20.01.2023	Date of last issue: 08.09.2021 Date of first issue: 26.10.2016	Print Date: 19.05.2025		
		for at least 10 minutes. If eye irritation persists, consult a s	pecialist.		
If swallowed		Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.	If accidentally swallowed obtain immediate medical attention. Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water. Aspiration hazard if swallowed - can enter lungs and cause		
4.2 Most	important symptom	s and effects, both acute and delayed			
Symptoms		: Inhalation may provoke the followir Unconsciousness Dizziness Drowsiness Headache Nausea Tiredness Skin contact may provoke the follow Erythema			
		Aspiration may cause pulmonary o	edema and pneumonitis.		
Risks	3	: Central nervous system depression Risk of product entering the lungs of Health injuries may be delayed. Causes skin irritation.			
4.3 Indica	4.3 Indication of any immediate medical attention and special treatment needed				

: Treat symptomatically.

SECTION 5: Firefighting measures

Treatment

5.1 Extinguishing media		
Suitable extinguishing media	:	ABC powder
Unsuitable extinguishing media	:	High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-	:	Fire Hazard
fighting		Do not let product enter drains.
		Contains gas under pressure; may explode if heated.
		Beware of vapours accumulating to form explosive concentra-
		tions. Vapours can accumulate in low areas.

Hazardous combustion prod- : Carbon oxides



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version 3.2	Revision Date: 20.01.2023		e of last issue: 08.09.2021 e of first issue: 26.10.2016	Print Date: 19.05.2025		
ucts			Nitrogen oxides (NOx) Metal oxides			
5.3 Advice	5.3 Advice for firefighters					
	al protective equipmen fighters	it :	In the event of fire, wear self-containe Use personal protective equipment. E tion products may be a hazard to hea	xposure to decomposi-		
Furthe	er information	:	Standard procedure for chemical fires Collect contaminated fire extinguishin must not be discharged into drains. Cool containers/tanks with water spra	g water separately. This		

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	 Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective equipment may intervene.
	equipment may intervene.

6.2 Environmental precautions

Environmental precautions	:	Do not allow contact with soil, surface or ground water. Prevent further leakage or spillage if safe to do so.
		If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible ab- sorbent material, (e.g. sand, earth, diatomaceous earth, ver- miculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal. Non-sparking tools should be used.
-------------------------	---	---

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version 3.2	Revision Date: 20.01.2023	Date of last issue: 08.09.2021 Date of first issue: 26.10.2016	Print Date: 19.05.2025
Advid	e on safe handling	equipment. Avoid contact with skin an For personal protection se Keep away from fire, spar Smoking, eating and drink plication area. Wash hands and face bef handling the product. Do not get in eyes or mou Do not get on skin or cloth Do not get on skin or cloth Do not use sparking tools These safety instructions may still contain product r Pressurized container: pro	r spray mist. tilation, wear suitable respiratory deves. ee section 8. ks and heated surfaces. king should be prohibited in the ap- ore breaks and immediately after th or on skin. hing. also apply to empty packaging which
Hygie	ene measures	: Wash face, hands and an handling.	y exposed skin thoroughly after
7.2 Condi	itions for safe storag	, including any incompatibiliti	es
Requ	irements for storage s and containers	: BEWARE: Aerosol is pres exposure and temperature or throw into fire even after	ssurized. Keep away from direct sun es over 50 °C. Do not open by force er use. Do not spray on flames or accordance with the particular na-
Stora	ige class (TRGS 510)	: 2B, Aerosol cans and ligh	ters
-	fic end use(s) ific use(s)	: Specific instructions for ha	andling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butane	106-97-8	AGW	1.000 ppm 2.400 mg/m3	DE TRGS 900 (2006-01-01)
	Peak-limit: excursion factor (category): 4;(II)			
propane	74-98-6	AGW	1.000 ppm 1.800 mg/m3	DE TRGS 900



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version	Revision Date:	Date of last issue: 08.09.2021	Print Date:
3.2	20.01.2023	Date of first issue: 26.10.2016	19.05.2025

	1			(2006-01-01)	
	Peak-limit: ex	cursion factor (categ	ory): 4;(II)	, ,	
distillates (petrole- um), hydrotreated heavy paraffinic	64742-54-7	AGW (Vapour and aerosols)	5 mg/m3	DE TRGS 900 (2018-06-07)	
		cursion factor (categ			
			s compliance with the OEL and of harming the unborn child	nd biological	
Distillates (petrole- um), solvent- dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0	AGW (Vapour and aerosols)	5 mg/m3	DE TRGS 900 (2018-06-07)	
	Peak-limit: excursion factor (category): 4;(II)				
			s compliance with the OEL an of harming the unborn child	nd biological	
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900 (2014-04-02)	
	Peak-limit: excursion factor (category): 2;(II) Further information: When there is compliance with the OEL and b				
				nd biological	
	tolerance valu		of harming the unborn child		
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900 (2014-04-02)	
	Peak-limit: excursion factor (category): 2;(II)				
			s compliance with the OEL and of harming the unborn child	nd biological	
isobutane	75-28-5	AGW	1.000 ppm 2.400 mg/m3	DE TRGS 900 (2006-01-01)	
	Peak-limit: ex	cursion factor (categ	ory): 4;(II)		

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
aluminium powder (stabi-	7429-90-5	Aluminium: 50 µg/g	In case of long-	TRGS 903
lised)		creatinine	term exposure:	(2019-03-
		(Urine)	after more than	29)
			one shift	

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health ef- fects	Value
distillates (petroleum), hydrotreated heavy paraffinic	Workers	Inhalation	Long-term local ef- fects	5,58 mg/m3
	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg
Distillates (petrole- um), solvent-dewaxed	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

3.2 20.01.2023 Date of first issue: 26.10.2016 19.05.2025	Version 3.2		Date of last issue: 08.09.2021 Date of first issue: 26.10.2016	Print Date: 19.05.2025	
---	----------------	--	---	---------------------------	--

heavy paraffinic; Baseoil — unspecified				
	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg
Hydrocarbons, C6- C7, n-alkanes, isoal- kanes, cyclics, <5% n-hexane	Workers	Skin contact	Long-term systemic effects	773 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	2035 mg/m3
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3,72 mg/m3
	Workers	Inhalation	Long-term local ef- fects	3,72 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
distillates (petroleum), hy-	Oral	9,33 mg/kg
drotreated heavy paraffinic		
Distillates (petroleum), solvent-	Oral	9,33 mg/kg
dewaxed heavy paraffinic;		
Baseoil — unspecified		

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation. Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection :	Safety glasses with side-shields
Hand protection Material : Break through time : Protective index :	butyl-rubber > 10 min Class 1
Remarks :	Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case. The selected protective gloves have to satisfy the specifica- tions of Regulation (EU) 2016/425 and the standard EN 374 derived from it.
Skin and body protection :	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Respiratory protection :	Use respiratory protection unless adequate local exhaust ven- tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version 3.2	Revision Date: 20.01.2023		te of last issue: 08.09.2021 te of first issue: 26.10.2016	Print Date: 19.05.2025
			Short term only	
Fil	ter type	:	Filter type A-P	
Protective measures		:	The type of protective equipment must b to the concentration and amount of the c at the specific workplace.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	aerosol
Colour	:	grey
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/range	:	No data available
Boiling point/boiling range	:	-44,5 °C (1.013 hPa)
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	10,9 %(V)
Lower explosion limit / Lower flammability limit	:	0,8 %(V)
Flash point	:	-97,00 °C Method: Abel-Pensky
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	< 20,5 mm2/s (40 °C)
Solubility(ies)		



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Versi 3.2	ion	Revision Date: 20.01.2023		ate of last issue: 08.09.2021Print Date:ate of first issue: 26.10.201619.05.2025	
	Water solubility		:	insoluble	
	Solubility in other solvents		s :	No data available	
Partition coefficient: n- octanol/water		:	No data available		
	Vapou	r pressure	:	4.750 hPa (20 °C)	
	Relative density		:	0,7 (20 °C) Reference substance: Water The value is calculated	
	Density		:	0,70 g/cm3 (20 °C)	
	Bulk density		:	No data available	
	Relative vapour density		:	No data available	
9.2 C	Other i	nformation			
	Explos	sives	:	Not explosive	
	Oxidizing properties		:	No data available	
	Self-ignition		:	not auto-flammable	
	Metal corrosion rate		:	Not corrosive to metals	
	Evaporation rate		:	No data available	
	Sublimation point		:	No data available	

SECTION 10: Stability and reactivity

10.1 Reactivity No hazards to be specially mentioned. 10.2 Chemical stability Stable under normal conditions. 10.3 Possibility of hazardous reactions Hazardous reactions No dangerous reaction known under conditions of normal use. 10.4 Conditions to avoid Conditions to avoid Heat, flames and sparks. Strong sunlight for prolonged periods. Risk of receptacle bursting.



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version	Revision Date:	Date of last issue: 08.09.2021	Print Date:
3.2	20.01.2023	Date of first issue: 26.10.2016	19.05.2025

10.5 Incompatible materials

Materials to avoid

: Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity		
Product:		
Acute oral toxicity	:	Remarks: Effects due to ingestion may include:
		Symptoms: Central nervous system depression
Acute inhalation toxicity	:	Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcot- ic effects.
		Remarks: Respiration of solvent vapour may cause dizziness.
		Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fa- tigue, Vertigo, Central nervous system depression
Acute dermal toxicity	:	Symptoms: Redness, Local irritation
Components:		
Hydrocarbons, C6-C7, n-alka	ane	es, isoalkanes, cyclics, <5% n-hexane:
Acute oral toxicity	:	LD50 (Rat): > 5.840 mg/kg Assessment: The substance or mixture has no acute oral tox- icity
Acute inhalation toxicity	:	LC50 (Rat): > 25,2 mg/l Exposure time: 4 h Test atmosphere: vapour Assessment: The substance or mixture has no acute inhala- tion toxicity
Acute dermal toxicity	:	LD50 (Rat): > 2,8 g/kg Assessment: The substance or mixture has no acute dermal toxicity
Kaolin, calcined:		
Acute inhalation toxicity	:	Assessment: The substance or mixture is classified as specific



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version 3.2	Revision Date: 20.01.2023	Date of last issue: 08.09.2021 Date of first issue: 26.10.2016	Print Date: 19.05.2025
		target organ toxicant, singl tory tract irritation.	le exposure, category 3 with respira-
buta	ne:		
Acute	e inhalation toxicity	: LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: gas	
distil	lates (petroleum), hy	drotreated heavy paraffinic:	
Acute	e oral toxicity	: LD50 (Rat): > 5.000 mg/kg Method: OECD Test Guide GLP: yes	
Acute	e inhalation toxicity	: LC50 (Rat): > 5,53 mg/l Exposure time: 4 h Test atmosphere: dust/mis Method: OECD Test Guide Assessment: The substand tion toxicity	
Acute	e dermal toxicity	: LD50 (Rabbit): > 5.000 mg Method: OECD Test Guide	
Disti	llates (petroleum), so	Ivent-dewaxed heavy paraffinic	; Baseoil — unspecified:
Acute	e oral toxicity	: LD50 (Rat): > 5.000 mg/kg Method: OECD Test Guide	
Acute	e dermal toxicity	: LD50 (Rabbit): > 5.000 mg Method: OECD Test Guide	
alum	inium powder (stabi	ised):	
Acute	e inhalation toxicity	: LC50 (Rat): > 5,09 mg/l Exposure time: 4 h Test atmosphere: dust/mis Assessment: The substand tion toxicity	st ce or mixture has no acute inhala-
isobi	utane:		
Acute	e inhalation toxicity	: LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: gas	
Skin	corrosion/irritation		
<u>Prod</u> Rema		: Irritating to skin.	



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version	Revision Date:	Date of last issue: 08.09.2021	Print Date:
3.2	20.01.2023	Date of first issue: 26.10.2016	19.05.2025

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

bit
ating to skin.
CD Test Guideline 404
ating to skin.

Kaolin, calcined:

Result

: Repeated exposure may cause skin dryness or cracking.

distillates (petroleum), hydrotreated heavy paraffinic:

Species	:	Rabbit
Assessment	:	No skin irritation
Method	:	OECD Test Guideline 404
Result	:	No skin irritation
GLP	:	yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:

Species	:	Rabbit
Assessment	:	No skin irritation
Method	:	OECD Test Guideline 404
Result	:	No skin irritation
GLP	:	yes

aluminium powder (stabilised):

Species	:	Rabbit
Assessment	:	No skin irritation
Result	:	No skin irritation

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species	:	Rabbit
Assessment	:	No eye irritation
Result	:	No eye irritation

Kaolin, calcined:

Result	:	Irritating to eyes.
--------	---	---------------------

distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version	Revision Date: 20.01.2023	Date of last issue: 08.09.2021	Print Date:
3.2		Date of first issue: 26.10.2016	19.05.2025

Assessment	: No eye irritation
Method	: OECD Test Guideline 405
Result	: No eye irritation
GLP	: yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

:	Rabbit No eye irritation OECD Test Guideline 405 No eye irritation
	yes
	:

aluminium powder (stabilised):

Species	:	Rabbit
Assessment	:	No eye irritation
Result	:	No eye irritation

Respiratory or skin sensitisation

Product:

Remarks

: This information is not available.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type :	Maximisation Test
Exposure routes :	Dermal
Species :	Guinea pig
Assessment	Does not cause skin sensitisation.
Method :	OECD Test Guideline 406
Result :	Did not cause sensitisation on laboratory animals.

distillates (petroleum), hydrotreated heavy paraffinic:

Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406
Result	:	Does not cause skin sensitisation.
GLP	:	yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406
Result	:	Does not cause skin sensitisation.
GLP	:	yes



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

sion	Revision Date: 20.01.2023	Date of last issue: 08.09.2021 Date of first issue: 26.10.2016	Print Date: 19.05.2025
alumir	nium powder (stabi	lised):	
Specie Assess Result	sment	 Guinea pig Did not cause sensitisation on Did not cause sensitisation on 	
Germ	cell mutagenicity		
<u>Produ</u>	<u>ct:</u>		
Genote	oxicity in vitro	: Remarks: No data available	
Genote	oxicity in vivo	: Remarks: No data available	
Comp	onents:		
Hydro	carbons, C6-C7, n-	alkanes, isoalkanes, cyclics, <5% n	-hexane:
Genoto	oxicity in vitro	: Test Type: Chromosome aber Test system: Rodent cell line Method: OECD Test Guideline Result: negative	
Distilla	ates (petroleum), s	olvent-dewaxed heavy paraffinic; Ba	aseoil — unspecified:
Genoto	oxicity in vitro	: Test system: Salmonella typhi Metabolic activation: with and Method: OECD Test Guideline Result: negative	without metabolic activation
Genoto	oxicity in vivo	: Species: Mouse Application Route: Oral Method: OECD Test Guideline Result: negative	ə 474
Carcin	ogenicity		
Produ	<u>ct:</u>		
Remar	ks	: No data available	
<u>Comp</u>	onents:		
distilla	ates (petroleum), h	drotreated heavy paraffinic:	
Carcin ment	ogenicity - Assess-	: Not classifiable as a human ca	arcinogen.
Distilla	ates (petroleum), s	olvent-dewaxed heavy paraffinic; Ba	aseoil — unspecified:
Specie		: Mouse	
Applies	ation Route	: Dermal : OECD Test Guideline 451	
Metho			



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

	20.01.2023	Dat	e of first issue: 26.10.2016	Print Date: 19.05.2025
Repro	ductive toxicity			
Produ	ct:			
	on fertility	:	Remarks: No data available	
Effects ment	on foetal develop-	:	Remarks: No data available	
<u>Comp</u>	onents:			
distilla	ates (petroleum), hy	drotre	eated heavy paraffinic:	
	ductive toxicity - As-	:		
sessme	ent		No toxicity to reproduction	
Distilla	ates (petroleum), so	lvent	-dewaxed heavy paraffinic; Base	eoil — unspecified:
Effects ment	on foetal develop-	:	Species: Rat Application Route: Dermal General Toxicity Maternal: NOAE Developmental Toxicity: NOAEL: Method: OECD Test Guideline 4 ²	30 mg/kg body weight
	- single exposure			
	onents:			
-		lkane	s, isoalkanes, cyclics, <5% n-he	
Assess	sment	:	May cause drowsiness or dizzine	ess.
Kaolin	, calcined:			
Exposi Assess	ure routes sment	:	Inhalation The substance or mixture is class toxicant, single exposure, catego irritation.	
STOT	- repeated exposure)		
	onents:			
Hydro	carbons, C6-C7. n-a	Ikane	s, isoalkanes, cyclics, <5% n-he	exane:
•	ure routes		inhalation (vapour) No significant health effects obse tions of 1 mg/l/6h/d or less.	
Repea	ted dose toxicity			
Produ	ct:			
<u></u>				



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version	Revision Date:	Date of last issue: 08.09.2021	Print Date:
3.2	20.01.2023	Date of first issue: 26.10.2016	19.05.2025

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

distillates (petroleum), hydrotreated heavy paraffinic:

No aspiration toxicity classification

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified: No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Furt	her	into	orma	tion	

Product:

Remarks

: Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

SECTION 12: Ecological information

12.1 Toxicity

Product:		
Toxicity to fish	:	Remarks: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic	:	Remarks: No data available



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

sion	Revision Date: 20.01.2023		e of last issue: 08.09.2021 e of first issue: 26.10.2016	Print Date: 19.05.2025
plants Toxicit	y to microorganisms	:		
			Remarks: No data available	
<u>Comp</u>	onents:			
	carbons, C6-C7, n-all y to fish	kane :	s, isoalkanes, cyclics, <5% n-hex LC50 (Oncorhynchus mykiss (rain Exposure time: 96 h Method: OECD Test Guideline 203 GLP: yes	bow trout)): > 22 mg/l
	y to daphnia and other c invertebrates	:	EL50 (Daphnia magna (Water flea Exposure time: 48 h Method: OECD Test Guideline 202 GLP: yes	
Toxicit plants	y to algae/aquatic	:	EbC50 (Pseudokirchneriella subca mg/l Exposure time: 72 h Method: OECD Test Guideline 207	
Ecoto	xicology Assessment	t		
Acute	aquatic toxicity	:	Toxic to aquatic life.	
Chron	ic aquatic toxicity	:	Toxic to aquatic life with long lastir	ng effects.
distilla	ates (petroleum), hyd	rotre	ated heavy paraffinic:	
	y to fish	:	LC50 (Pimephales promelas (fathe Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203 GLP: yes	
	y to daphnia and other c invertebrates	:	EC50 (Daphnia magna (Water flea Exposure time: 48 h Test Type: Immobilization Method: OECD Test Guideline 202 GLP: yes	
	y to daphnia and other c invertebrates (Chron- city)		NOEC: 10 mg/l Exposure time: 21 d Species: Daphnia magna (Water f Test Type: semi-static test Method: OECD Test Guideline 217 GLP: yes	

Distillates (petroleulii), sc	vent-dewaked heavy paramine, baseon — dispecified.	
Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l	



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version 3.2	Revision Date: 20.01.2023		e of last issue: 08.09.2021 e of first issue: 26.10.2016	Print Date: 19.05.2025
			Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203 GLP: yes	3
	ity to daphnia and other ic invertebrates	· :	EC50 (Daphnia magna (Water flea Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202	
Toxic plants	ity to algae/aquatic	:	NOEC (Pseudokirchneriella subcaj mg/l Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201	
	ity to daphnia and other ic invertebrates (Chron icity)		NOEC: 10 mg/l Exposure time: 21 d Species: Daphnia magna (Water fl	ea)
alum	inium powder (stabilis	ed):	:	
Toxic	ity to fish	:	LC50 (Oncorhynchus mykiss (raint Exposure time: 96 h Test Type: static test Remarks: No toxicity at the limit of	
Ecoto	oxicology Assessmen	t		
Acute	aquatic toxicity	:	This product has no known ecotoxi	icological effects.
Chror	nic aquatic toxicity	:	This product has no known ecotoxi	icological effects.
12.2 Persi	stence and degradabi	lity		
Prod	uct:			
Biode	gradability	:	Remarks: No data available	
Physi ity	co-chemical removabil-	:	Remarks: No data available	
Com	oonents:			

Components:

Hydrocarbons, C6-C7, n-alka	ane	s, isoalkanes, cyclics, <5% n-hexane:
Biodegradability	:	Result: Readily biodegradable.

distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability	:	Test Type: aerobic
		Inoculum: activated sludge
		Result: Not rapidly biodegradable
		Biodegradation: 3 %
		Exposure time: 28 d



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKE 33	E A			
OKS 23	ר <u>ר</u>			
Version 3.2	Revision Date: 20.01.2023		e of last issue: 08.09.2021 e of first issue: 26.10.2016	Print Date: 19.05.2025
			Method: OECD Test Guideline 301 GLP: yes	В
Disti	llates (petroleum), sol	vent	-dewaxed heavy paraffinic; Baseo	il — unspecified:
	egradability	:	Test Type: aerobic Inoculum: activated sludge Result: Not rapidly biodegradable Biodegradation: 31 % Exposure time: 28 d Method: OECD Test Guideline 301 GLP: yes	
12.3 Bioa	ccumulative potential			
Prod	uct:			
	ccumulation	:	Remarks: This mixture contains no be persistent, bioaccumulating and This mixture contains no substance persistent and very bioaccumulatin	toxic (PBT). e considered to be very
<u>Com</u>	ponents:			
buta	ne:			
	ion coefficient: n- nol/water	:	log Pow: 2,89 Method: OECD Test Guideline 107	
prop	ane:			
	ion coefficient: n- nol/water	:	log Pow: 2,36	
distil	lates (petroleum), hvo	Irotro	eated heavy paraffinic:	
Partit	ion coefficient: n- nol/water	:	log Pow: > 2	
isobı	utane:			
	tion coefficient: n- nol/water	:	log Pow: 2,88 Method: OECD Test Guideline 107	
12.4 Mob	ility in soil			
Prod	uct:			
Mobi		:	Remarks: No data available	
	bution among environ- al compartments	:	Remarks: No data available	



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version	Revision Date:	Date of last issue: 08.09.2021	Print Date:
3.2	20.01.2023	Date of first issue: 26.10.2016	19.05.2025

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

distillates (petroleum), hydro	otre	eated heavy paraffinic:
Assessment	:	Non-classified vPvB substance. Non-classified PBT substance

12.6 Endocrine disrupting properties

	Ρι	rod	uc	t:
--	----	-----	----	----

Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-	:	Harmful to aquatic life with long lasting effects.
mation		

SECTION 13: Disposal considerations

13.1 Waste treatment methods	
Product :	Do not dispose of with domestic refuse. Dispose of as hazardous waste in compliance with local and national regulations.
	Waste codes should be assigned by the user based on the application for which the product was used.
Contaminated packaging :	Packaging that is not properly emptied must be disposed of as the unused product. Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.
	The following Waste Codes are only suggestions:
Waste Code :	unused product, packagings not completely emptied 16 05 04*, gases in pressure containers (including halons) containing hazardous substances



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version	Revision Date:	Date of last issue: 08.09.2021	Print Date:
3.2	20.01.2023	Date of first issue: 26.10.2016	19.05.2025

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	UN 1950
ADR	:	UN 1950
RID	:	UN 1950
IMDG	:	UN 1950
ΙΑΤΑ	:	UN 1950
14.2 UN proper shipping name		
ADN	:	AEROSOLS
ADR	:	AEROSOLS
RID	:	AEROSOLS
IMDG	:	AEROSOLS
ΙΑΤΑ	:	Aerosols, flammable
14.3 Transport hazard class(es)		
ADN	:	2
ADR	:	2
RID	:	2
IMDG	:	2.1
ΙΑΤΑ	:	2.1
14.4 Packing group		
ADN Packing group Classification Code Labels	:	Not assigned by regulation 5F 2.1
ADR Packing group Classification Code Labels Tunnel restriction code	: : : : : : : : : : : : : : : : : : : :	Not assigned by regulation 5F 2.1 (D)
RID Packing group Classification Code Hazard Identification Number Labels IMDG Packing group Labels		Not assigned by regulation 5F 23 2.1 Not assigned by regulation 2.1
	·	_



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version 3.2	Revision Date: 20.01.2023	Date of last issue: 08.09.2021Print Date:Date of first issue: 26.10.201619.05.2025		
Em	S Code	: F-D, S-U		
Pac airc Pac	A (Cargo) king instruction (cargo raft) king instruction (LQ) king group els	 203 Y203 Not assigned by regulation Flammable Gas 		
Pac ger Pac	A (Passenger) king instruction (passen- aircraft) king instruction (LQ) king group els	 203 Y203 Not assigned by regulation Flammable Gas 		
14.5 Env	vironmental hazards			
	ironmentally hazardous	: no		
ADI Env	R ironmentally hazardous	: no		
RID Env	ironmentally hazardous	: no		
IMD Mar	IG ine pollutant	: no		
14.6 Spe	ecial precautions for us	er		
The transport classification(s) provided herein are for informational purposes only, and solely				

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks

: Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC)	: This product does not contain sub- stances of very high concern (Regu- lation (EC) No 1907/2006 (REACH), Article 57).
REACH - List of substances subject to authorisation (Annex XIV) (EU. REACH-Annex XIV)	: Not applicable



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version 3.2	Revision Date: 20.01.2023	Date of last issue: 08. Date of first issue: 26.		Print Date: 19.05.2025
plete th	ation (EC) No 1005/2 he ozone layer 005/2009)	009 on substances that o	de- :	Not applicable
	recast)	on persistent organic po	ollu- :	Not applicable
ment a	and the Council conce gerous chemicals	12 of the European Parli erning the export and im		Not applicable
	ation (EU) 2019/1148 ives precursors	on the marketing and u	se of :	Listed
all sus ances tional o https:// fairs/fil terroris precur- sors/do	picious transactions, and thefts should be contact point. Please /ec.europa.eu/home- es/what-we-do/polici sm/explosives/explos	affairs/sites/ homeaf- es/crisis-and-	ır- na-	aluminium powder (stabilised) (ANNEX II)
			: P2	
Parlian	nent and of the Cour accident hazards inv	8/EU of the European icil on the control of olving dangerous sub-	P3a	FLAMMABLE AEROSOLS
			18	Liquefied extremely flammable gases (including LPG) and natural gas
			34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar proper- ties as regards flammability and environmental hazards as the products referred to in points (a) to (d)
Water	hazard class (Germa	a- : WGK 2 obviously	hazardo	



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Vers 3.2	sion	Revision Date: 20.01.2023		e of last issue: 08.09.2021 e of first issue: 26.10.2016	Print Date: 19.05.2025
	ny)			Classification according to AwSV, Annex	1 (5.2)
	TA Luf	t List (Germany)	:	Total dust: others: 2,53 %	
				Inorganic substances in powdered form: Not applicable Inorganic substances in vapour or gaseou Not applicable Organic Substances: portion Class 1: 0,16 % others: 89,82 %	us form:
				Carcinogenic substances: Not applicable Mutagenic: Not applicable Toxic to reproduction: Not applicable	
	Volatile	e organic compounds	:	Directive 2010/75/EU of 24 November 20 emissions (integrated pollution prevention Volatile organic compounds (VOC) conte	and control)

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

EUH066	:	Repeated exposure may cause skin dryness or cracking.
H220	:	Extremely flammable gas.
H225	:	Highly flammable liquid and vapour.
H228	:	Flammable solid.
H280	:	Contains gas under pressure; may explode if heated.
H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H411	:	Toxic to aquatic life with long lasting effects.
EUH066	:	Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version	Revision Date:	Date of last issue: 08.09.2021	Print Date:
3.2	20.01.2023	Date of first issue: 26.10.2016	19.05.2025

Note C	:	Some organic substances may be marketed either in a specif- ic isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the sub- stance is a specific isomer or a mixture of isomers.
Note L	:	The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determi- nation of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method"Institute of Petroleum, Lon- don), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.
Note T	:	This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regula- tion show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, in- cluding reference to the relevant test method(s) shall be in- cluded in the safety data sheet.
Note U (table 3.1)	:	When put on the market gases have to be classified as "Gas- es under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is pack- aged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903	:	TRGS 903 - Biological limit values
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good La-



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



OKS 2351

Version	Revision Date:	Date of last issue: 08.09.2021	Print Date:
3.2	20.01.2023	Date of first issue: 26.10.2016	19.05.2025

boratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixtu	ire:	Classification procedure:
Aerosol 1	H222, H229	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
STOT SE 3	H336	Based on product data or assessment
Asp. Tox. 1	H304	Based on product data or assessment
Aquatic Chronic 3	H412	Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.

