Fax: 0049-(0)7223-284-245



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.06.2015 Version number 15 Revision: 21.06.2015

SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: UHU plus endfest 300 (Binder)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0 email: info@uhu.boltongroup.de

· Further information obtainable from: CRD

· 1.4 Emergency telephone number: Tel.: +49 (0) 72 23/28 40

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS07 GHS09

· Signal word Warning

· Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

(Contd. of page 1)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.06.2015 Version number 15 Revision: 21.06.2015

Trade name: UHU plus endfest 300 (Binder)

P102 Keep out of reach of children.

P103 Read label before use.

Avoid breathing dust/fume/gas/mist/vapours/sprav. P261

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Avoid release to the environment. P273 P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

Contains epoxy constituents. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

•		
· Dangerous components:		
CAS: 25068-38-6 NLP: 500-033-5 Reg.nr.: 01-2119456619-26-0002	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) ♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
	reaction product: bisphenol-F-(epichlorhydrin)	
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)



Printing date 24.06.2015 Version number 15 Revision: 21.06.2015

Trade name: UHU plus endfest 300 (Binder)

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water spray

Carbon dioxide

Foam

Fire-extinguishing powder

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

- 5.3 Advice for firefighters
- Protective equipment:

Do not inhale explosion gases or combustion gases.

No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures

 Ensure adequate ventilation
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Store in cool, dry place in tightly closed receptacles.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

- · Storage class: 12
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)



Printing date 24.06.2015 Version number 15 Revision: 21.06.2015

Trade name: UHU plus endfest 300 (Binder)

(Contd. of page 3)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Avoid direct contact with the chemical/ the product/ the preparation by organisational measures.

- Respiratory protection: Not necessary if room is well-ventilated.
- Protection of hands:

Rubber gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical properties • General Information • Appearance:

Form: Fluid Colour: Colourless

Odour: Weak, characteristicOdour threshold: Not determined.

· pH-value at 20 °C:

Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: Undetermined.

Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature:

Decomposition temperature: Not determined.

(Contd. on page 5)



Printing date 24.06.2015 Version number 15 Revision: 21.06.2015

Trade name: UHU plus endfest 300 (Binder)

	(Contd. of page
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
Density at 20 °C:	1,15 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wa	nter): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	40000 s (DIN 53211/4)
· Solvent content:	
Organic solvents:	0,0 %
VOC (EC)	0,00 %
Solids content:	91,0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Exothermic polymerisation.

Reacts with amines.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity
- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 24.06.2015 Version number 15 Revision: 21.06.2015

Trade name: UHU plus endfest 300 (Binder)

(Contd. of page 5)

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name	
ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)) 3082 UMWELTGEFÄHRDENDER STOFF, FLÜSSIG, N.A.G. (Reaktionsprodukt: Bisphenol-A-Fnichlorhydrinharze, mit durchschnittlichem

Molekulargewicht ≤ 700, Bisphenol-F-

(Contd. on page 7)



Printing date 24.06.2015 Version number 15 Revision: 21.06.2015

Trade name: UHU plus endfest 300 (Binder)

IMDG		
ENVIRON MENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenot-A-(epichlorhydrin): epoxy resin (number average molecular weight ≤ 700), reaction product bisphenot-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenot-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenot-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)) 14.3 Transport hazard class(es) ADR, IMDG, IATA III 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenot-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Marine pollutant: Yes Special marking (ADR): Special marking (ADR): Special marking (ADR): Special marking (ATA): Special marking (ATA): Yes Symbol (fish and tree) Symbol (fish and tree) Symbol fish and tree) Symbol fish and tree) Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Excepted quantities (EQ) FA,S-F Tunnel restriction code E IMDG Import in the packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 30 ml Maximum net quantity per outer packaging: 30 ml Maximum net quantity per outer packaging: 30 ml		(Contd. of page 6
SUBSTANCE, L(QUID, N.O.S. (reaction product bisphenol-A-(epichiorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product bisphenol-F-(epichiorhydrin) epoxy resin (number average molecular weight ≤ 700), MARINE POLLUTANT IATA IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, L(QUID, N.O.S. (reaction product bisphenol-A-(epichiorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product bisphenol-F-(epichiorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product bisphenol-F-(epichiorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product bisphenol-F-(epichiorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product bisphenol-F-(epichiorhydrin); epoxy resin (number average molecular weight ≤ 700). **Class 9 Miscellaneous dangerous substances and articles. 9 14.4 Packing group ADR, IMDG, IATA III 14.5 Environmental hazards: **Product contains environmentally hazardous substances: reaction product: bisphenol-A (epichiorhydrin); epoxy resin (number average molecular weight ≤ 700) **Yes **Special marking (ADR): **Special marking (ADR): **Special marking (ADR): **Special marking (ATA): **Special marking (ADR):	· · IMDG	
bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT EN VIRON MENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)) 14.3 Transport hazard class(es) ADR, IMDG, IATA 11. 12. 13. Environmental hazards: 14.4 Packing group ADR, IMDG, IATA 11. 14.5 Environmental hazards: 14.6 Special marking (ADR): 14.6 Special marking (IATA): 15. Symbol (fish and tree) 16. Symbol (fish and tree) 17. Symbol (fish and tree) 18. Symbol (fish and tree) 19. Symbol (fish and tree) 19. Symbol fish and tree) 19. Symbol fish and tree) 19. Symbol fish and tree) 19. EMS Number: 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 17. Transport in bulk according to Annex II of Marpol and the IBC Code 18. Code: E1 19. Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 30 ml	2 C	
average molecular weight ≤ 700), MARINE POLLUTANT IATA IA		
average molecular weight ≤ 700)), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenol-A-(epichlorhydrin): epoxy resin (number average molecular weight ≤ 700), reaction product bisphenol-F-(epichlorhydrin): epoxy resin (number average molecular weight ≤ 700). 14.3 Transport hazard class(es) ADR, IMDG, IATA Class 9 Miscellaneous dangerous substances and articles. 9 14.4 Packing group ADR, IMDG, IATA III 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Marine pollutant: Special marking (ADR): Special marking (IATA): Special marking (IATA): Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree) Transport on bulk according to Annex II of Marpol and the IBC Code Not applicable. Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (LQ) Fixensport category Tunnel restriction code E IMDG Limited quantities (LQ) Excepted quantities (L		average molecular weight ≤ 700), reaction product:
IATA POLLUTANT		
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenol-A-(epichiorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product bisphenol-F-(epichiorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product bisphenol-F-(epichiorhydrin); epoxy resin (number average molecular weight ≤ 700), ADR, IMDG, IATA Libie Substances and articles 9 11.4 Packing group ADR, IMDG, IATA 11.5 Environmental hazards: Marine pollutant: Special marking (ADR); Symbol (fish and tree) Special marking (IATA); Symbol (fish and tree) Symbol (fish		
SUBSTANCE. LIQUID. N.O.S. (reaction product bisphenol-A-(epichlorhydrin): epoxy resin (number average molecular weight ≤ 700), reaction product bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)) 14.3 Transport hazard class(es) ADR, IMDG, IATA 111 122 Class 9 Miscellaneous dangerous substances and articles. 9 Marine pollutant: Yes Symbol (fish and tree) Special marking (ADR): Symbol (fish and tree) Symbol (fish and tree) Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F 11.7 Transport in bulk according to Annex II of Marpol and the IBC Code 1 Marpol and the IBC Code 1 More and articles. 1 Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 30 ml Maximum net quantity per outer packaging: 30 ml		
bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)) 14.3 Transport hazard class(es) ADR, IMDG, IATA Class 9 Miscellaneous dangerous substances and articles. 9 14.4 Packing group ADR, IMDG, IATA III 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Marine pollutant: Special marking (ADR): Special mar	·IAIA	
average molecular weight ≤ 700), reaction product bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)) 14.3 Transport hazard class(es) ADR, IMDG, IATA Label 9 Miscellaneous dangerous substances and articles. 9 14.4 Packing group ADR, IMDG, IATA III 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-Ar (epichlorhydrin): epoxy resin (number average molecular weight ≤ 700) Warine pollutant: Special marking (ADR): Special marking (IATA): Symbol (fish and tree) Symbol (fish and tree) 14.6 Special precautions for user Danger code (Kemler): Danger code (Kemler): EMS Number: 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (LQ) I Transport category Tunnel restriction code E IMDG Limited quantities (LQ) Awimum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packagi		
bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)) 14.3 Transport hazard class(es) ADR, IMDG, IATA Class Jaking group ADR, IMDG, IATA 11.4 Packing group ADR, IMDG, IATA 11.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Marine pollutant: Special marking (ADR): Symbol (fish and tree) Special marking (IATA): Symbol (fish and tree) Special marking (IATA): Symbol (fish and tree) Special precautions for user Danger code (Kemler): Danger code (Kemler): EMS Number: 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (LQ) Limited quantities (LQ) Limited quantities (LQ) Limited quantities (LQ) Excepted quantities (LQ)		
average molecular weight ≥ 700)) 14.3 Transport hazard class(es) ADR, IMDG, IATA Label 9 14.4 Packing group ADR, IMDG, IATA 11.5 Environmental hazards: Product contains environmentally hazardous substances and environmentally hazardous substances: reaction product: bisphenol-A (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Yes Symbol (fish and tree) Special marking (ADR): Special marking (ATA): Special marking (ATA): Special marking (ATA): Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree) Not special marking (ATA): Symbol (fish and tree) S		
- 14.3 Transport hazard class(es) - ADR, IMDG, IATA - Label - Class - Label - 14.4 Packing group - ADR, IMDG, IATA - 14.5 Environmental hazards: - Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700 class) - Marine pollutant: - Special marking (ADR): - Special marking (IATA): - Symbol (fish and tree) - Symbol (fish and tree) - Symbol (fish and tree) - 14.6 Special precautions for user - Danger code (Kemler): - Dang		
ADR, IMDG, IATA Label 9 Miscellaneous dangerous substances and articles. 9 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Yes Symbol (fish and tree) Symbol (fish and tree) Special marking (ADR): Special marking (IATA): Symbol (fish and tree) 14.6 Special precautions for user Danger code (Kemler): 90 F-A,S-F 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (LQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (LQ) Excepted quantities (LQ) Excepted quantities (LQ) Limited quantities (LQ) Limited quantities (LQ) Excepted quantities (LQ) Limited quantities (· 14.3 Transport hazard class(es)	<u> </u>
Class - Label - 14.4 Packing group - ADR, IMDG, IATA - 14.5 Environmental hazards: - Warine pollutant: - Special marking (ADR): - Special marking (IATA): - 14.6 Special precautions for user - Danger code (Kemler): - EMS Number: - 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code - Transport/Additional information: - ADR - Limited quantities (LQ) - Excepted quantities (LQ) - Transport category - Tunnel restriction code - EMDG - Limited quantities (LQ) - Excepted quantities (LQ) - Excepted quantities (LQ) - Excepted quantities (EQ) - Excepted quantities (EQ) - Excepted quantit	•	
articles. 9 14.4 Packing group ADR, IMDG, IATA III 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Marine pollutant: Special marking (ADR): Special marking (IATA): Special marking (IATA): Symbol (fish and tree) Symbol (fish and tree) 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. Danger code (Kemler): 90 EMS Number: 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code Imaximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 1000 ml Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) Limited quantities (EQ) SL Excepted quantities (EQ) SL Excepted quantities (EQ) Adaximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		
articles. 9 14.4 Packing group ADR, IMDG, IATA III 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Marine pollutant: Special marking (ADR): Special marking (IATA): Special marking (IATA): Symbol (fish and tree) Symbol (fish and tree) 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. Danger code (Kemler): 90 EMS Number: 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code Imaximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 1000 ml Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) Limited quantities (EQ) SL Excepted quantities (EQ) SL Excepted quantities (EQ) Adaximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	₩ \	
articles. 9 14.4 Packing group ADR, IMDG, IATA III 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Marine pollutant: Special marking (ADR): Special marking (IATA): Special marking (IATA): Symbol (fish and tree) Symbol (fish and tree) 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. Danger code (Kemler): 90 EMS Number: 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code Imaximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 1000 ml Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) Limited quantities (EQ) SL Excepted quantities (EQ) SL Excepted quantities (EQ) Adaximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	1	
articles. 9 14.4 Packing group ADR, IMDG, IATA III 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Marine pollutant: Special marking (ADR): Special marking (IATA): Special marking (IATA): Symbol (fish and tree) Symbol (fish and tree) 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. Danger code (Kemler): 90 EMS Number: 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code Imaximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 1000 ml Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) Limited quantities (EQ) SL Excepted quantities (EQ) SL Excepted quantities (EQ) Adaximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	y	
Label 9 14.4 Packing group ADR, IMDG, IATA III 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-Adepiclently drin); epoxy resin (number average molecular weight ≤ 700) Marine pollutant: Yes Special marking (ADR): Symbol (fish and tree) Special marking (IATA): Symbol (fish and tree) Special marking (IATA): Symbol (fish and tree) 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. Danger code (Kemler): 90 EMS Number: F-A,S-F 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. Transport/Additional information: ADR Limited quantities (LQ) 5L Excepted quantities (EQ) 5L Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) 5L Excepted quantities (LQ) 5L Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) 5D Excepted quantities (LQ) 5D Excepted Quantitie	· Class	9 Miscellaneous dangerous substances and
14.4 Packing group ADR, IMDG, IATA 11.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Marine pollutant: Yes Symbol (fish and tree) Special marking (ADR): Special marking (IATA): Symbol (fish and tree) 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. Danger code (Kemler): EMS Number: F-A, S-F 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) Excepted quantities (EQ) 5 L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 30 ml Maximum net quantity per outer packaging: 1000	Label	
ADR, IMDG, IĀTA 11.5 Environmental hazards: 14.5 Environmental hazards: 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-Ark (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Yes Symbol (fish and tree) Special marking (ADR): Special marking (IATA): Symbol (fish and tree) 14.6 Special precautions for user Danger code (Kemler): EMS Number: 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (LQ) Limited quantities (LQ) Excepted quantities (LQ) Limited quantities (LQ) Excepted quantities (LQ) Excepted quantities (LQ) Limited quantities (LQ) Excepted quantities (LQ) Excepted quantities (LQ) Excepted quantities (LQ) Limited quantities (LQ) Excepted quantities (LQ) Aximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		9
. 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Yes Symbol (fish and tree) Special marking (ADR): Special marking (IATA): Symbol (fish and tree) 14.6 Special precautions for user Danger code (Kemler): EMS Number: 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code Limited quantities (LQ) Transport category Tunnel restriction code E IMDG Limited quantities (LQ) Excepted quantities (EQ) SL Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantities (LQ) Excepted quantities (LQ) Limited quantities (LQ) Excepted quantities (LQ) Assimum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		
substances: reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Yes Symbol (fish and tree) Special marking (ADR): Special marking (IATA): Symbol (fish and tree) 14.6 Special precautions for user Danger code (Kemler): EMS Number: 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code Limited quantities (LQ) Transport category Tunnel restriction code Limited quantities (LQ) Excepted quantities (LQ) The code E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 30 ml		
(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Marine pollutant: Yes Symbol (fish and tree) Special marking (ADR): Special marking (IATA): Symbol (fish and tree) 14.6 Special precautions for user Danger code (Kemler): EMS Number: F-A, S-F 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (LQ) Transport category Tunnel restriction code E IMDG Limited quantities (LQ) Excepted quantities (EQ) SL Code: E1 Maximum net quantity per inner packaging: 30 ml Maximut net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	· 14.5 Environmental hazards:	
Marine pollutant: Marine pollutant: Special marking (ADR): Special marking (IATA): Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree) 14.6 Special precautions for user Danger code (Kemler): EMS Number: F-A,S-F 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (LQ) Tansport category Tunnel restriction code E Maximum net quantity per inner packaging: 30 ml Maximum net restriction code E Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantities (LQ) Excepted quantities (LQ) Excepted quantities (EQ) SL Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		
Marine pollutant: Special marking (ADR): Special marking (IATA): Special marking (IATA): 14.6 Special precautions for user Danger code (Kemler): EMS Number: 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (LQ) Transport category Tunnel restriction code Limited quantities (LQ) Excepted quantities (LQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 1000 ml Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml		
Special marking (ADR): Special marking (IATA): Special marking (IATA): Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree) 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. 90 EMS Number: F-A,S-F 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category 3 Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (EQ) SL Excepted quantities (LQ) Excepted quantities (LQ) Excepted quantities (LQ) Limited quantities (LQ) Excepted quantities (LQ) Excepted quantities (LQ) Excepted quantities (LQ) Excepted quantities (LQ) Excepted quantities (LQ) Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	· Marine pollutant·	- · · · · · · · · · · · · · · · · · · ·
Special marking (ADR): Special marking (IATA): Symbol (fish and tree) 14.6 Special precautions for user Danger code (Kemler): EMS Number: F-A,S-F 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (EQ) SL Excepted quantities (LQ) Transport category SL IMDG Limited quantities (LQ) Excepted quantities (EQ) Excepted quantities (LQ) Limited quantities (LQ) Excepted quantities (LQ) Limited quantities (LQ) Excepted quantities (LQ) Limited quantities (LQ) Excepted quantities (LQ)	maine pondant.	
Special marking (IATA): Symbol (fish and tree) 14.6 Special precautions for user Danger code (Kemler): EMS Number: 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (EQ) SL Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 30 ml Maximum net quantity per outer packaging: 30 ml Maximum net quantity per outer packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	· Special marking (ADR):	
Danger code (Kemler): EMS Number: - 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code - Transport/Additional information: - ADR - Limited quantities (LQ) - Excepted quantities (EQ) - Transport category - Transport category - Tunnel restriction code - IMDG - Limited quantities (LQ) - Excepted quantities (LQ) - Excepted quantities (LQ) - Code: E1 - Maximum net quantity per inner packaging: 1000 - ml - Transport category - Tunnel restriction code - Limited quantities (LQ) - Excepted quantities (LQ) - Excepted quantities (LQ) - Excepted quantities (EQ) - Maximum net quantity per inner packaging: 30 ml - Maximum net quantity per inner packaging: 30 ml - Maximum net quantity per inner packaging: 30 ml - Maximum net quantity per outer packaging: 1000		
Danger code (Kemler): EMS Number: - 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code - Transport/Additional information: - ADR - Limited quantities (LQ) - Excepted quantities (EQ) - Transport category - Transport category - Tunnel restriction code - IMDG - Limited quantities (LQ) - Excepted quantities (LQ) - Excepted quantities (LQ) - Code: E1 - Maximum net quantity per inner packaging: 1000 - ml - Transport category - Tunnel restriction code - Limited quantities (LQ) - Excepted quantities (LQ) - Excepted quantities (LQ) - Excepted quantities (EQ) - Maximum net quantity per inner packaging: 30 ml - Maximum net quantity per inner packaging: 30 ml - Maximum net quantity per inner packaging: 30 ml - Maximum net quantity per outer packaging: 1000	· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances
EMS Number: In the second sec		and articles.
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. Transport/Additional information: ADR Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		
of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (LQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml Tcansport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	· EMS Number:	F-A,S-F
Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (EQ) Tcode: E1 Maximum net quantity per inner packaging: 1000 ml 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) - Transport category - Tunnel restriction code - Limited quantities (LQ) - Excepted quantities (LQ) - Excepted quantities (LQ) - Excepted quantities (EQ) - Maximum net quantity per inner packaging: 30 ml - Maximum net quantity per inner packaging: 30 ml - Maximum net quantity per inner packaging: 30 ml - Maximum net quantity per outer packaging: 30 ml - Maximum net quantity per outer packaging: 1000	•	Not applicable.
Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code Limited quantities (LQ) Excepted quantities (LQ) Excepted quantities (LQ) Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	Transport/Additional information:	
Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml Transport category Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		
Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		
Maximum net quantity per outer packaging: 1000 ml Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	Excepted quantities (EQ)	
Transport category 3 Tunnel restriction code E IMDG Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		
Transport category Tunnel restriction code E IMDG Limited quantities (LQ) Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		
Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (EQ) SUBJECTION SETTING TO SETTING TO SETTING THE PROPRIET OF THE P	. Transport category	****
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	Tunnel restriction code	
Limited quantities (LQ) Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		<u> </u>
Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		El
Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		
Maximum net quantity per outer packaging: 1000	Excepted quantities (EQ)	
, ,,		
		(Contd. on page 8



Printing date 24.06.2015 Version number 15 Revision: 21.06.2015

Trade name: UHU plus endfest 300 (Binder)

	(Contd. of page 7)
	ml
· UN "Model Regulation":	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing MSDS: CRD

· Contact:

Frau A. Liar,

Herr Dr. C. Hanf

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

* * Data compared to the previous version altered.

Fax: 0049-(0)7223-284-245



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.06.2015 Version number 17 Revision: 21.06.2015

SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: UHU plus endfest 300 (Härter)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0

Tel.:0049-(0)7223-284-0 email: info@uhu.boltongroup.de

- · Further information obtainable from: CRD
- · 1.4 Emergency telephone number: Tel.: +49 (0) 72 23/28 40

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine amine, polyethylenepoly-,triethylenetetramine fraction

· Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)



Printing date 24.06.2015 Version number 17 Revision: 21.06.2015

Trade name: UHU plus endfest 300 (Härter)

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

· Dangero	us components:		
CAS: 105		N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	5,0-<10%
EINECS:	234-148-4	Skin Corr. 1B, H314; Eye Dam. 1, H318; (1) Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	
CAS: 906 EINECS: Reg.nr.: 0		amine, polyethylenepoly-,triethylenetetramine fraction Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	5,0-<10%

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product. Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing:

Rinse out mouth and then drink plenty of water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water spray

Carbon dioxide

Foam

(Contd. on page 3)



Printing date 24.06.2015 Version number 17 Revision: 21.06.2015

Trade name: UHU plus endfest 300 (Härter)

(Contd. of page 2)

Fire-extinguishing powder

Use fire extinguishing methods suitable to surrounding conditions.

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

- 5.3 Advice for firefighters
- Protective equipment:

Do not inhale explosion gases or combustion gases.

No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Send for recovery or disposal in suitable receptacles.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Store in cool, dry place in tightly closed receptacles.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

- Storage class: 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

90640-67-8 amine, polyethylenepoly-,triethylenetetramine fraction

MAK (Germany) als Dampf und Aerosol;vgl.Abschn.IV

Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)



Printing date 24.06.2015 Version number 17 Revision: 21.06.2015

Trade name: UHU plus endfest 300 (Härter)

(Contd. of page 3)

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Avoid direct contact with the chemical/ the product/ the preparation by organisational measures.

· Protection of hands:

Rubber gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

SECTION 9	· Physica	I and chemical	Inroperties
SECTION 3	. FIIVSICA	ı alıu tilelilital	NI UNEI LIES

· 9.1 Information on basic physical · General Information	and chemical properties
· Appearance:	
Form:	Fluid
Colour:	Yellow
· Odour:	Amine-like
· Odour threshold:	Not determined.
· pH-value at 20 °C:	12 (1:1 in H2O)
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	278 °C
· Flash point:	135 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	335 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	0,95 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.

(Contd. on page 5)



Printing date 24.06.2015 Version number 17 Revision: 21.06.2015

Trade name: UHU plus endfest 300 (Härter)

		(Contd. of page 4
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
Partition coefficient (n-octano	I/water): Not determined.	
· Viscosity:		
Dynamic at 20 °C:	32500 mPas	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0,0 %	
VOC (EC)	0,00 %	
Solids content:	84,2 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

· LD/LC5	· LD/LC50 values relevant for classification:		
90640-6	90640-67-8 amine, polyethylenepoly-,triethylenetetramine fraction		
Oral	LD50	2500 mg/kg (rat)	
Dermal	LD50	805 mg/kg (rabbit)	

- Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 6)



Printing date 24.06.2015 Version number 17 Revision: 21.06.2015

Trade name: UHU plus endfest 300 (Härter)

(Contd. of page 5)

- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

· 14.1 UN-Number · ADR, IMDG, IATA	UN2735
· 14.2 UN proper shipping name · ADR	2735 POLYAMINES, LIQUID, CORROSIV N.O.S. (N'-(3-aminopropyl)-N,N-dimethylpropar 1,3-diamine, TRIETHYLENETETRAMINE) 1760 ÄTZENDER FLÜSSIGER STOFF, N.A. (N'-(3-Aminopropyl)-N,N-dimethylpropan-1,
· IMDG, IATA	diamin, TRIETHYLENTETRAMIN) POLYAMINES, LIQUID, CORROSIVE, N.O.S. (I (3-aminopropyl)-N,N-dimethylpropane-1, diamine, TRIETHYLENETETRAMINE)
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class · Label	8 Corrosive substances. 8
· 14.4 Packing group · ADR, IMDG, IATA	II

(Contd. on page 7)



Printing date 24.06.2015 Version number 17 Revision: 21.06.2015

Trade name: UHU plus endfest 300 (Härter)

	(Contd. of page
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Corrosive substances.
Danger code (Kemler):	80
EMS Number:	F-A,S-B
· Segregation groups	Alkalis
· 14.7 Transport in bulk according to An	nex II
of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
_	Maximum net quantity per outer packaging: 500 m
Transport category	2
Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	1 kg
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 m
· UN "Model Regulation":	UN2735, POLYAMINES, LIQUID, CORROSIVE
	N.O.S. (N'-(3-aminopropyl)-N,N-dimethylpropane
	1,3-diamine, TRIETHYLENETETRAMINE), 8, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

- Department issuing MSDS: CRD
- · Contact:

Frau A. Liar,

Herr Dr. C. Hanf

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 8)



Printing date 24.06.2015 Version number 17 Revision: 21.06.2015

Trade name: UHU plus endfest 300 (Härter)

(Contd. of page 7)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

* Data compared to the previous version altered.