



Muttersprenger Baureihe 54-C



**Zweischneidige Muttersprenger 54-2-C und 54-3-C
zum Sprengen von unlösbaren Muttern in der Güteklasse 5, 6 und 8**



Wofür wird ein Muttersprenger benötigt?


Um festsitzende, beschädigte oder überdrehte Muttern, ohne den Gewindebolzen zu beschädigen, zu sprengen.



Um die Darstellung zu verbessern wurde auf die Unfallschutzpläne verzichtet.
Dies entspricht nicht den KUKKO-Sicherheitsvorschriften - siehe unten!

Art. No.	 M	 mm	 mm	 mm	 mm	Ersatzteil Meißel
54-2-C	6-18	10-27	14	109	17	54-2-M-C
54-3-C	12-24	17-36	16	134	19	54-3-M-C

TECHNOLOGIE





Einzigartiges, leichtes Zurückdrehen des Muttersprenger-Meißels aus verformten oder gesprengten Muttern.
Der Meißel bleibt nicht in der Mutter hängen.

ERSATZMEISSEL



Die Sprengmeißel der Muttersprenger sind Verschleißteile, sie unterliegen nicht der Garantie.
Stumpfe, schartige oder ausgebrochene Meißel sind sofort auszutauschen.
Halten Sie die Spindel des Muttersprengers immer sauber und gut gefettet.

SICHERHEITSHINWEISE



Alle Sicherheits- und Gebrauchshinweise zum Download



100



Nut splitters series 54-C



**Double-edged mechanical nut splitters 54-2-C and 54-3-C
for splitting grade 5, 6 and 8 irretrievable nuts.**



What is a nut splitter needed for?


For splitting particularly large tight or over-twisted nuts
without damaging the bolt thread.



Images for advertising purpose only – pullers and other tools are not shown in use!
This does not comply with the KUKKO precautionary notes and helpful hints - see below!

Art. No.	 M	 mm	 mm	 mm	 mm	spare part chisel
54-2-C	6-18	10-27	14	109	17	54-2-M-C
54-3-C	12-24	17-36	16	134	19	54-3-M-C

TECHNOLOGY



Unique, simple pullback of the nut splitter chisel to remove it
from deformed or split nuts. This means that the chisel does
not get caught in the nut.

SPARE PART CHISEL






The splitting chisels of the nut splitters
are wearing parts, they are not covered
by the guarantee.

Blunt, pitted or broken chisels must be
replaced immediately.

Keep the thread of the splitting chisels clean
and well oiled.

PRECAUTIONARY NOTES



You can download all precautionary notes and helpful hints here



100