

PDF technical sheet

7026UADG/GNP42U3G



High precision angular contact ball bearings

High precision angular contact ball bearing, moulded polyamide cage centred on balls

Product definition	
d	5.1181 "
D	7.8740 "
B	1.2992 "
d1	6.0591 "
d2	5.8465 "
D1	6.9370 "
D2	7.3622 "
a	2.1732 "
Contact angle, α	25 °
rs min	0.0787 "
r1s min	0.0394 "
f0	16.1
Precision class	P42
Mass	11.46 oz
Brand	NTN



Product performance	
Dynamic load, C	126 kN
Static load, C0	136 kN
Nlim (oil)	9,900 RPM
Nlim (grease)	6,200 RPM
Preload level	GN
Peload value	1,270 kN
axial rigidity	390 N/ μ m
radial rigidity	830 N/ μ m
Min operating temperature, Tmin	-4 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.90 Hz
Characteristic outer ring frequency, BPF0	9.75 Hz
Characteristic inner ring frequency, BPF1	12.25 Hz



Abutment dimensions

da min	5.5118 "
Da max	7.4803 "
Db max	7.6575 "
r1a max	0.0394 "
ra max	0.0787 "
D6	6.0591 "

Calculation factors

Equivalent dynamic radial load

$$P = X.Fr + Y.Fa$$

Series			e	Single or DT bearing arrangement				DB or DF arrangement			
				Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
				X	Y	X	Y	X	Y	X	Y
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°	0.178	0.38	1	0	0.44	1.47	1	1.65	0.72	2.39
		0.357	0.4				1.4		1.57		2.28
		0.714	0.43				1.3		1.46		2.11
		1.07	0.46				1.23		1.38		2
		1.43	0.47				1.19		1.34		1.93
		2.14	0.5				1.12		1.26		1.82
		3.57	0.55				1.02		1.14		1.66
		5.35	0.56						1.12		1.63
		7.14	0.56				1		1.12		1.63
	25°		0.68	1	0	0.41	0.87	1	0.92	0.67	1.41
	30°		0.8								0.78

Equivalent static radial load

$$Po = Xo.Fr + Yo.Fa$$

Series			Single or DT bearing arrangement		DB or DF arrangement	
			Xo	Yo	Xo	Yo
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°		0.5	0.46	1	0.92
	25°			0.38		0.76
	30°			0.33		0.66

For single or DT bearing arrangement :

If $Po < Fr$, then use $Po = Fr$