

PDF technical sheet 7028HVUJ74



High precision angular contact ball bearings

High precision angular contact ball bearing, laminated resin cage centred on outer ring

Product definition	
d	5.5118 "
D	8.2677 "
B	1.2992 "
d1	6.4016 "
D1	7.7990 "
D2	7.3789 "
a	2.2441 "
Contact angle, α	25 °
rs min	0.0787 "
r1s min	0.0394 "
f0	16.235
Precision class	P4
Mass	12.06 oz
Brand	SNR



Product performance	
Dynamic load, C	128 kN
Static load, C0	144 kN
Fatigue limit load, Cu	6.10 kN
Nlim (oil)	9,100 RPM
Nlim (grease)	6,000 RPM
Axial displacement K Factor	0.38
Preload level	7
Peload value	1,650 kN
axial rigidity	450 N/ μ m
radial rigidity	949 N/ μ m
Min operating temperature, Tmin	-22 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	8.38 Hz
Characteristic outer ring frequency, BPF0	10.27 Hz
Characteristic inner ring frequency, BPF1	12.73 Hz



Abutment dimensions

da min	5.9055 "
db min	5.9055 "
Da max	7.8740 "
Db max	7.8740 "
r1a max	0.0394 "
ra max	0.0787 "
D6	6.6142 "

Calculation factors

Equivalent dynamic radial load

$$P = X \cdot Fr + Y \cdot Fa$$

Series			e	Single or DT bearing arrangement				DB or DF arrangement			
				Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
				X	Y	X	Y	X	Y	X	Y
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°	0.178	0.38	1	0	0.44	1.47	1	1.65	0.72	2.39
		0.357	0.4				1.4		1.57		2.28
		0.714	0.43				1.3		1.46		2.11
		1.07	0.46				1.23		1.38		2
		1.43	0.47				1.19		1.34		1.93
		2.14	0.5				1.12		1.26		1.82
		3.57	0.55				1.02		1.14		1.66
		5.35	0.56						1.12		1.63
		7.14	0.56				1		1.12		1.63
	25°		0.68			0.41	0.87		0.92	0.67	1.41
	30°		0.8			0.39	0.76		0.78	0.63	1.24

Equivalent static radial load

$$P_0 = X_0 \cdot Fr + Y_0 \cdot Fa$$

Series			Single or DT bearing arrangement		DB or DF arrangement	
			X ₀	Y ₀	X ₀	Y ₀
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°		0.5	0.46	1	0.92
	25°			0.38		0.76
	30°			0.33		0.66

For single or DT bearing arrangement :

If $P_0 < Fr$, then use $P_0 = Fr$