

PDF technical sheet

71936HVUJ74A



High precision angular contact ball bearings

High precision angular contact ball bearing, laminated resin cage centred on outer ring

Product definition	
d	7.0866 "
D	9.8425 "
B	1.2992 "
d1	8.0157 "
D1	8.9143 "
D2	9.3103 "
a	2.6378 "
Contact angle, α	25 °
rs min	0.0787 "
r1s min	0.0394 "
f0	16.874
Precision class	P4
Mass	15.03 oz
Brand	SNR



Product performance	
Dynamic load, C	125 kN
Static load, C0	166 kN
Fatigue limit load, Cu	6.40 kN
Nlim (oil)	7,400 RPM
Nlim (grease)	4,900 RPM
Axial displacement K Factor	0.32
Preload level	7
Peloid value	1,850 kN
axial rigidity	544 N/ μ m
radial rigidity	1,147 N/ μ m
Min operating temperature, Tmin	-22 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.46 Hz
Characteristic rolling element frequency, BSF	11.21 Hz
Characteristic outer ring frequency, BPF0	13.80 Hz
Characteristic inner ring frequency, BPF1	16.21 Hz



Abutment dimensions

da min	7.4803 "
db min	7.4803 "
Da max	9.4488 "
Db max	9.4488 "
r1a max	0.0394 "
ra max	0.0787 "
D6	8.2008 "

Calculation factors

Equivalent dynamic radial load

$$P = X \cdot Fr + Y \cdot Fa$$

Series			e	Single or DT bearing arrangement				DB or DF arrangement			
				Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
				X	Y	X	Y	X	Y	X	Y
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°	0.178	0.38	1	0	0.44	1.47	1	1.65	0.72	2.39
		0.357	0.4				1.4		1.57		2.28
		0.714	0.43				1.3		1.46		2.11
		1.07	0.46				1.23		1.38		2
		1.43	0.47				1.19		1.34		1.93
		2.14	0.5				1.12		1.26		1.82
		3.57	0.55				1.02		1.14		1.66
		5.35	0.56						1.12		1.63
		7.14	0.56				1		1.12		1.63
	25°		0.68			0.41	0.87		0.92	0.67	1.41
	30°		0.8			0.39	0.76		0.78	0.63	1.24

Equivalent static radial load

$$Po = Xo \cdot Fr + Yo \cdot Fa$$

Series			Single or DT bearing arrangement		DB or DF arrangement	
			X ₀	Y ₀	X ₀	Y ₀
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°		0.5	0.46	1	0.92
	25°			0.38		0.76
	30°			0.33		0.66

For single or DT bearing arrangement :

If $Po < Fr$, then use $Po = Fr$