PDF technical sheet
6211ZZC3/5C



Single row deep groove ball bearings
Deep groove ball bearing, radial contact, pressed steel cage, shields on both sides

Product definition	
d	2.1654 "
D	3.9370 "
B	0.8268 "
rs min	0.0591 "
Radial clearance class	C3
Mass	2.12 oz
Brand	NTN



Product performance	
Dynamic load, C	43.50 kN
Static load, C0	29.20 kN
Fatigue limit load, Cu	1.33 kN
f0	14.3
Nlim (grease)	6,400 RPM
Min operating temperature, Tmin	−22 °C
Max operating temperature, Tmax	347 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.24 Hz
Characteristic outer ring frequency, BPF0	4.08 Hz
Characteristic inner ring frequency, BPFI	5.92 Hz



NTN-SNR ROULEMENTS – www.ntn-snr.com
1 rue des Usines – 74010 Annecy Cedex – France – Tel. +33 (0)4 50 65 30 00
S.A. au capital de 123 599 542 € - RCS ANNECY B 325 821 072 – Id. Fiscale : FR 48 325 821 072 – SIRET 325 821 072 00015 –
Code APE 2815 Z – Code NACE 28.15

Abutment dimensions	
da min	2.4803 "
Da max	3.6220 "
ra max	0.0591 "

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr