

## PDF technical sheet 624ZZC3/L519



### Single row deep groove ball bearings

Deep groove ball bearing, radial contact, pressed steel cage, shields on both sides

| Product definition     |          |
|------------------------|----------|
| d                      | 0.1575 " |
| D                      | 0.5118 " |
| B                      | 0.1969 " |
| rs min                 | 0.0079 " |
| Radial clearance class | C3       |
| Mass                   | 0.01 oz  |
| Brand                  | NTN      |



| Product performance             |            |
|---------------------------------|------------|
| Dynamic load, C                 | 1.31 kN    |
| Static load, C0                 | 0.49 kN    |
| Fatigue limit load, Cu          | 0.02 kN    |
| f0                              | 12.4       |
| Nlim (grease)                   | 42,000 RPM |
| Min operating temperature, Tmin | -22 °C     |
| Max operating temperature, Tmax | 392 °C     |



### Abutment dimensions

|        |          |
|--------|----------|
| da min | 0.2205 " |
| Da max | 0.4488 " |
| ra max | 0.0079 " |

### Calculation factors

#### Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

| $\frac{f_0 F_a}{C_0}$ | e    | $F_a / F_r \leq e$ |   | $F_a / F_r > e$ |      |
|-----------------------|------|--------------------|---|-----------------|------|
|                       |      | X                  | Y | X               | Y    |
| 0.172                 | 0.19 | 1                  | 0 | 0.56            | 2.3  |
| 0.345                 | 0.22 |                    |   |                 | 1.99 |
| 0.689                 | 0.26 |                    |   |                 | 1.71 |
| 1.03                  | 0.28 |                    |   |                 | 1.55 |
| 1.38                  | 0.3  |                    |   |                 | 1.45 |
| 2.07                  | 0.34 |                    |   |                 | 1.31 |
| 3.45                  | 0.38 |                    |   |                 | 1.15 |
| 5.17                  | 0.42 |                    |   |                 | 1.04 |
| 6.89                  | 0.44 |                    |   |                 | 1    |

#### Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

| $X_0$ | $Y_0$ |
|-------|-------|
| 0.6   | 0.5   |

For single or DT bearing arrangement :

If  $P_0 < F_r$ , then use  $P_0 = F_r$