

PDF technical sheet 6318L1C4




Single row deep groove ball bearings

Deep groove ball bearing, radial contact, machined cage, open


Product definition

d	3.5433 "
D	7.4803 "
B	1.6929 "
rs min	0.1181 "
Radial clearance class	C4
Mass	17.32 oz
Brand	NTN



Product performance

Dynamic load, C	143 kN
Static load, C0	107 kN
Fatigue limit load, Cu	4.10 kN
f0	13.3
Nlim (oil)	4,200 RPM
Nlim (grease)	3,600 RPM
Min operating temperature, Tmin	-76 °C
Characteristic cage frequency, FTF	0.39 Hz
Characteristic rolling element frequency, BSF	4.18 Hz
Characteristic outer ring frequency, BPF0	3.09 Hz
Characteristic inner ring frequency, BPF1	4.91 Hz



Abutment dimensions

da min	4.0551 "
Da max	6.9685 "
ra max	0.0984 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If $P_0 < F_r$, then use $P_0 = F_r$