

PDF technical sheet 6856C3



Single row deep groove ball bearings

Deep groove ball bearing, radial contact, pressed steel cage, open

Product definition

d	11.0236 "
D	13.7795 "
B	1.2992 "
rs min	0.0787 "
Radial clearance class	C3
Mass	26.10 oz
Brand	NTN



Product performance

Dynamic load, C	137 kN
Static load, C0	177 kN
Fatigue limit load, Cu	4.55 kN
f0	16.1
Nlim (oil)	1,900 RPM
Nlim (grease)	1,600 RPM
Min operating temperature, Tmin	-76 °C
Characteristic cage frequency, FTF	0.47 Hz
Characteristic rolling element frequency, BSF	14.63 Hz
Characteristic outer ring frequency, BPF0	11.18 Hz
Characteristic inner ring frequency, BPF1	12.82 Hz



Abutment dimensions

da min	11.3780 "
Da max	13.4252 "
ra max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If $P_0 < F_r$, then use $P_0 = F_r$