



PDF technical sheet 6002NZZ




Single row deep groove ball bearings

Deep groove ball bearing, radial contact, pressed steel cage, snap ring groove on outer diameter, shields on both sides

Product definition	
d	0.5906 "
D	1.2598 "
B	0.3543 "
d1	0.8071 "
D1	1.1339 "
a min	0.0811 "
a max	0.0748 "
rs min	0.0118 "
rNs min	0.0118 "
D3 max	1.1870 "
b min	0.0531 "
b max	0.0650 "
r0 max	0.0157 "
Radial clearance class	CN
Mass	0.11 oz
Brand	SNR



Product performance	
Dynamic load, C	5.40 kN
Static load, C0	2.85 kN
Fatigue limit load, Cu	0.13 kN
f0	13.9
Nref	22,000 RPM
Nlim	31,000 RPM
Min operating temperature, Tmin	-4 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.40 Hz
Characteristic rolling element frequency, BSF	4.73 Hz
Characteristic outer ring frequency, BPF0	3.59 Hz
Characteristic inner ring frequency, BPF1	5.41 Hz



Abutment dimensions

da min	0.6693 "
da max	0.8071 "
Da max	1.1811 "
ra max	0.0118 "
rNa max	0.0118 "
Db min	1.4764 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement ;

If $P_0 < F_r$, then use $P_0 = F_r$