


PDF technical sheet 6310.NR




Single row deep groove ball bearings

Product definition	
d	1.9685 "
D	4.3307 "
B	1.0630 "
d1	2.5472 "
D1	3.8583 "
a min	0.1209 "
a max	0.1291 "
Ca min	0.2138 "
Ca max	0.2260 "
rs min	0.0787 "
rNs min	0.0197 "
D3 max	4.2051 "
b min	0.1063 "
b max	0.1181 "
r0 max	0.0236 "
D4 max	4.5906 "
f	0.0949 "
Snap ring reference	R110
Radial clearance class	CN
Mass	3.77 oz
Brand	SNR



Product performance	
Dynamic load, C	61.30 kN
Static load, C0	38.30 kN
Fatigue limit load, Cu	1.74 kN
f0	13.2
Nref	7,700 RPM
Nlim	10,000 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.07 Hz
Characteristic outer ring frequency, BPF0	3.07 Hz
Characteristic inner ring frequency, BPF1	4.93 Hz



Abutment dimensions

da min	2.3228 "
Da max	3.9764 "
ra max	0.0787 "
rNa max	0.0197 "
Db min	4.6457 "

349/702/3/en/DGBB.jpg