


PDF technical sheet 7334BGM




Single row or matched pairs of angular contact ball bearings

Angular contact ball bearing, brass cage ball guided

Product definition	
d	6.6929 "
D	14.1732 "
B	2.8346 "
d1	9.6693 "
d2	7.5354 "
D1	11.2480 "
D2	13.3071 "
a	5.7874 "
Contact angle, α	40 °
rs min	0.1575 "
r1s min	0.0591 "
Radial clearance class	CN
Mass	121.14 oz
Brand	SNR



Product performance	
Dynamic load, C	392 kN
Static load, C0	509 kN
Fatigue limit load, Cu	14.20 kN
Nref	2,000 RPM
Nlim	2,300 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	4.36 Hz
Characteristic outer ring frequency, BPF0	5.39 Hz
Characteristic inner ring frequency, BPF1	7.61 Hz



Abutment dimensions	
da min	7.4016 "
db min	7.4016 "
Da max	13.4646 "
Db max	13.8386 "
r1a max	0.0591 "
ra max	0.1181 "

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

	e	Single or DT bearing arrangement				DB or DF arrangement			
		Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y	X	Y	X	Y
30°	0.8	1	0	0.9	0.76	1	0.78	0.63	1.24
40°	1.14			0.35	0.57		0.55	0.57	0.93

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

a	Single or DT bearing arrangement		DB or DF arrangement	
	X ₀	Y ₀	X ₀	Y ₀
30°	0.5	0.33	1	0.66
40°		0.26		0.52

For single or DT bearing arrangement :

If $P_0 < F_r$, then use $P_0 = F_r$