

PDF technical sheet N214




Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, pressed steel cage

Product definition	
d	2.7559 "
D	4.9213 "
B	0.9449 "
E	4.3504 "
F	3.3268 "
d1	3.5276 "
rs min	0.0591 "
r1s min	0.0591 "
Radial clearance class	CN
Mass (without HJ ring)	4.23 oz
Brand	NTN



Product performance	
Dynamic load, C	83.50 kN
Static load, C0	95 kN
Fatigue limit load, Cu	11.60 kN
Nlim (oil)	6,500 RPM
Nlim (grease)	5,500 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C



Abutment dimensions	
da min	3.0709 "
Da max	4.6063 "
Db min	4.4488 "
Dc max	4.2913 "
ra max	0.0591 "
r1a max	0.0591 "

Calculation factors

Equivalent dynamic radial load

$$P = F_r$$

Equivalent static radial load

$$P_0 = F_r$$

NTN-SNR ROULEMENTS – www.ntn-snr.com

1 rue des Usines – 74010 Annecy Cedex – France – Tel. +33 (0)4 50 65 30 00

S.A. au capital de 123 599 542 € - RCS ANNECY B 325 821 072 - Id. Fiscale : FR 48 325 821 072 – SIRET 325 821 072 00015 –

Code APE 2815 Z – Code NACE 28.15