

PDF technical sheet N316G1C3




Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, brass cage

Product definition	
d	3.1496 "
D	6.6929 "
B	1.5354 "
E	5.7874 "
F	4.0551 "
d1	4.4016 "
rs min	0.0827 "
r1s min	0.0827 "
Radial clearance class	C3
Mass (without HJ ring)	14.57 oz
Brand	NTN



Product performance	
Dynamic load, C	190 kN
Static load, C0	207 kN
Fatigue limit load, Cu	23.60 kN
Nlim (oil)	4,800 RPM
Nlim (grease)	4,100 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C



Abutment dimensions	
da min	3.5827 "
Da max	6.2598 "
Db min	5.9449 "
Dc max	5.7087 "
ra max	0.0787 "
r1a max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$P = F_r$

Equivalent static radial load

$P_0 = F_r$

NTN-SNR ROULEMENTS – www.ntn-snr.com

1 rue des Usines – 74010 Annecy Cedex – France – Tel. +33 (0)4 50 65 30 00

S.A. au capital de 123 599 542 € - RCS ANNECY B 325 821 072 - Id. Fiscale : FR 48 325 821 072 – SIRET 325 821 072 00015 –

Code APE 2815 Z – Code NACE 28.15