


PDF technical sheet N318G1




Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, brass cage

Product definition	
d	3.5433 "
D	7.4803 "
B	1.6929 "
E	6.4961 "
F	4.5276 "
d1	4.9213 "
rs min	0.1181 "
r1s min	0.1181 "
Radial clearance class	CN
Mass (without HJ ring)	19.58 oz
Brand	NTN



Product performance	
Dynamic load, C	240 kN
Static load, C0	265 kN
Fatigue limit load, Cu	29.20 kN
Nlim (oil)	4,300 RPM
Nlim (grease)	3,700 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C



Abutment dimensions	
da min	4.0551 "
Da max	6.9685 "
Db min	6.6535 "
Dc max	6.4173 "
ra max	0.0984 "
r1a max	0.0984 "

Calculation factors

Equivalent dynamic radial load

$$P = F_r$$

Equivalent static radial load

$$P_0 = F_r$$

NTN-SNR ROULEMENTS – www.ntn-snr.com

1 rue des Usines – 74010 Annecy Cedex – France – Tel. +33 (0)4 50 65 30 00

S.A. au capital de 123 599 542 € - RCS ANNECY B 325 821 072 - Id. Fiscale : FR 48 325 821 072 – SIRET 325 821 072 00015 –

Code APE 2815 Z – Code NACE 28.15