

PDF technical sheet

N324




Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, pressed steel cage

Product definition	
d	4.7244 "
D	10.2362 "
B	2.1654 "
E	8.8976 "
F	6.0630 "
d1	6.6339 "
rs min	0.1181 "
r1s min	0.1181 "
Radial clearance class	CN
Mass (without HJ ring)	46.56 oz
Brand	NTN



Product performance	
Dynamic load, C	450 kN
Static load, C0	510 kN
Fatigue limit load, Cu	51.30 kN
Nlim (oil)	3,200 RPM
Nlim (grease)	2,700 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C



Abutment dimensions	
da min	5.2362 "
Da max	9.7244 "
Db min	9.0157 "
Dc max	8.8189 "
ra max	0.0984 "
r1a max	0.0984 "

Calculation factors

Equivalent dynamic radial load

$$P = F_r$$

Equivalent static radial load

$$P_0 = F_r$$

NTN-SNR ROULEMENTS – www.ntn-snr.com

1 rue des Usines – 74010 Annecy Cedex – France – Tel. +33 (0)4 50 65 30 00

S.A. au capital de 123 599 542 € - RCS ANNECY B 325 821 072 - Id. Fiscale : FR 48 325 821 072 - SIRET 325 821 072 00015 -

Code APE 2815 Z - Code NACE 28.15