

PDF technical sheet NJ1014G1




Single row cylindrical roller bearings

Single row cylindrical roller bearing, single direction for axial loads, separable, brass cage.

Product definition	
d	2.7559 "
D	4.3307 "
B	0.7874 "
E	3.9370 "
F	3.1496 "
d1	3.3071 "
rs min	0.0433 "
r1s min	0.0394 "
Radial clearance class	CN
Mass (without HJ ring)	2.43 oz
Brand	NTN



Product performance	
Dynamic load, C	58.50 kN
Static load, C0	70.50 kN
Fatigue limit load, Cu	8.60 kN
Nlim (oil)	7,600 RPM
Nlim (grease)	6,500 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	8.89 Hz
Characteristic outer ring frequency, BPF0	8.89 Hz
Characteristic inner ring frequency, BPF1	11.11 Hz



Abutment dimensions	
da min	3.0118 "
da max	3.0709 "
dc min	3.3465 "
Da max	4.0748 "
ra max	0.0394 "

Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$P_0 = Fr$$