

## PDF technical sheet NJ2306EG1C3



### Single row cylindrical roller bearings

Single row cylindrical roller bearing, single direction for axial loads, separable, brass cage.

| Product definition     |          |
|------------------------|----------|
| d                      | 1.1811 " |
| D                      | 2.8346 " |
| B                      | 1.0630 " |
| E                      | 2.4606 " |
| F                      | 1.5945 " |
| d1                     | 1.7677 " |
| rs min                 | 0.0433 " |
| r1s min                | 0.0433 " |
| Radial clearance class | C3       |
| Mass (without HJ ring) | 1.86 oz  |
| Brand                  | NTN      |



| Product performance                           |           |
|-----------------------------------------------|-----------|
| Dynamic load, C                               | 74.50 kN  |
| Static load, C0                               | 77.50 kN  |
| Fatigue limit load, Cu                        | 9.50 kN   |
| Nlim (oil)                                    | 9,700 RPM |
| Nlim (grease)                                 | 8,300 RPM |
| Min operating temperature, Tmin               | -40 °C    |
| Max operating temperature, Tmax               | 248 °C    |
| Characteristic cage frequency, FTF            | 0.39 Hz   |
| Characteristic rolling element frequency, BSF | 4.47 Hz   |
| Characteristic outer ring frequency, BPF0     | 4.72 Hz   |
| Characteristic inner ring frequency, BPF1     | 7.28 Hz   |



| Abutment dimensions |          |
|---------------------|----------|
| da min              | 1.4370 " |
| da max              | 1.5748 " |
| dc min              | 1.8898 " |
| Da max              | 2.5787 " |
| ra max              | 0.0394 " |

### Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$P_0 = Fr$$