

PDF technical sheet NJ328EG1



Single row cylindrical roller bearings

Single row cylindrical roller bearing, single direction for axial loads, separable, brass cage.

Product definition	
d	5.5118 "
D	11.8110 "
B	2.4409 "
E	10.3937 "
F	7.0866 "
d1	7.7480 "
rs min	0.1575 "
r1s min	0.1575 "
Radial clearance class	CN
Mass (without HJ ring)	75.13 oz
Brand	NTN



Product performance	
Dynamic load, C	665 kN
Static load, C0	795 kN
Fatigue limit load, Cu	76.50 kN
Nlim (oil)	2,400 RPM
Nlim (grease)	2,100 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.10 Hz
Characteristic outer ring frequency, BPF0	5.68 Hz
Characteristic inner ring frequency, BPF1	8.32 Hz



Abutment dimensions	
da min	6.1417 "
da max	6.9291 "
dc min	7.7953 "
Da max	11.1811 "
ra max	0.1181 "

Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$P_0 = Fr$$