

## PDF technical sheet NU214EG1C3



### Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, brass cage

| Product definition     |          |
|------------------------|----------|
| d                      | 2.7559 " |
| D                      | 4.9213 " |
| B                      | 0.9449 " |
| E                      | 4.4685 " |
| F                      | 3.2874 " |
| rs min                 | 0.0591 " |
| r1s min                | 0.0591 " |
| Radial clearance class | C3       |
| Mass (without HJ ring) | 4.25 oz  |
| Brand                  | NTN      |



| Product performance                           |           |
|-----------------------------------------------|-----------|
| Dynamic load, C                               | 119 kN    |
| Static load, C0                               | 137 kN    |
| Fatigue limit load, Cu                        | 16.70 kN  |
| Nlim (oil)                                    | 5,900 RPM |
| Nlim (grease)                                 | 5,000 RPM |
| Min operating temperature, Tmin               | -40 °C    |
| Max operating temperature, Tmax               | 248 °C    |
| Characteristic cage frequency, FTF            | 0.42 Hz   |
| Characteristic rolling element frequency, BSF | 6.41 Hz   |
| Characteristic outer ring frequency, BPF0     | 7.21 Hz   |
| Characteristic inner ring frequency, BPF1     | 9.79 Hz   |



| Abutment dimensions |          |
|---------------------|----------|
| da min              | 3.0709 " |
| da max              | 3.2283 " |
| db min              | 3.3858 " |
| Da max              | 4.6063 " |
| ra max              | 0.0591 " |
| r1a max             | 0.0591 " |

### Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$P_0 = Fr$$