



## PDF technical sheet NU2307ET2XC3




### Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, polyamide cage

| Product definition     |          |
|------------------------|----------|
| d                      | 1.3780 " |
| D                      | 3.1496 " |
| B                      | 1.2205 " |
| E                      | 2.7638 " |
| F                      | 1.8189 " |
| rs min                 | 0.0591 " |
| r1s min                | 0.0433 " |
| Radial clearance class | C3       |
| Mass (without HJ ring) | 2.63 oz  |
| Brand                  | NTN      |



| Product performance                           |           |
|-----------------------------------------------|-----------|
| Dynamic load, C                               | 99 kN     |
| Static load, C0                               | 109 kN    |
| Fatigue limit load, Cu                        | 13.30 kN  |
| Nlim (oil)                                    | 8,500 RPM |
| Nlim (grease)                                 | 7,200 RPM |
| Min operating temperature, Tmin               | -40 °C    |
| Max operating temperature, Tmax               | 248 °C    |
| Characteristic cage frequency, FTF            | 0.40 Hz   |
| Characteristic rolling element frequency, BSF | 4.64 Hz   |
| Characteristic outer ring frequency, BPF0     | 5.16 Hz   |
| Characteristic inner ring frequency, BPF1     | 7.84 Hz   |



| Abutment dimensions |          |
|---------------------|----------|
| da min              | 1.6339 " |
| da max              | 1.7717 " |
| db min              | 1.8898 " |
| Da max              | 2.8346 " |
| ra max              | 0.0591 " |
| r1a max             | 0.0394 " |

### Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$P_0 = Fr$$