

PDF technical sheet NU252C3



Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, brass cage

Product definition	
d	10.2362 "
D	18.8976 "
B	3.1496 "
E	16.5354 "
F	12.5984 "
rs min	0.1969 "
r1s min	0.1969 "
Radial clearance class	C3
Mass (without HJ ring)	268.08 oz
Brand	NTN



Product performance	
Dynamic load, C	1,150 kN
Static load, C0	1,660 kN
Fatigue limit load, Cu	137 kN
Nlim (oil)	1,600 RPM
Nlim (grease)	1,300 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	7.27 Hz
Characteristic outer ring frequency, BPF0	8.22 Hz
Characteristic inner ring frequency, BPF1	10.78 Hz



Abutment dimensions	
da min	11.0236 "
da max	12.5197 "
db min	12.7165 "
Da max	18.1102 "
ra max	0.1575 "
r1a max	0.1575 "

Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$P_0 = Fr$$