

PDF technical sheet NU313EG1CM



Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, brass cage

Product definition	
d	2.5591 "
D	5.5118 "
B	1.2992 "
E	4.9016 "
F	3.2480 "
rs min	0.0827 "
r1s min	0.0827 "
Radial clearance class	CM
Mass (without HJ ring)	8.36 oz
Brand	NTN



Product performance	
Dynamic load, C	181 kN
Static load, C0	191 kN
Fatigue limit load, Cu	23.10 kN
Nlim (oil)	5,400 RPM
Nlim (grease)	4,600 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.40 Hz
Characteristic rolling element frequency, BSF	4.73 Hz
Characteristic outer ring frequency, BPF0	5.18 Hz
Characteristic inner ring frequency, BPF1	7.82 Hz



Abutment dimensions	
da min	2.9921 "
da max	3.1890 "
db min	3.3465 "
Da max	5.0787 "
ra max	0.0787 "
r1a max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$P_0 = Fr$$