



## PDF technical sheet NUP211




### Single row cylindrical roller bearings

Single row cylindrical roller bearing, locating, separable, pressed steel cage

| Product definition     |          |
|------------------------|----------|
| d                      | 2.1654 " |
| D                      | 3.9370 " |
| B                      | 0.8268 " |
| E                      | 3.4843 " |
| F                      | 2.6181 " |
| d1                     | 2.7874 " |
| rs min                 | 0.0591 " |
| r1s min                | 0.0433 " |
| Radial clearance class | CN       |
| Mass (without HJ ring) | 2.37 oz  |
| Brand                  | NTN      |



| Product performance             |           |
|---------------------------------|-----------|
| Dynamic load, C                 | 58 kN     |
| Static load, C0                 | 62.50 kN  |
| Fatigue limit load, Cu          | 7.60 kN   |
| Nlim (oil)                      | 8,200 RPM |
| Nlim (grease)                   | 6,900 RPM |
| Min operating temperature, Tmin | -40 °C    |
| Max operating temperature, Tmax | 248 °C    |



| Abutment dimensions |          |
|---------------------|----------|
| da min              | 2.4803 " |
| dc min              | 2.8740 " |
| Da max              | 3.6220 " |
| ra max              | 0.0591 " |

### Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$P_0 = Fr$$