


PDF technical sheet NUP213EHTG1NRC3




Single row cylindrical roller bearings

Single row cylindrical roller bearing with snap ring, separable, locating, brass cage

Product definition	
d	2.5591 "
D	4.7244 "
B	0.9055 "
E	4.2717 "
F	3.0906 "
d1	3.3268 "
a min	0.1520 "
a max	0.1598 "
Ca min	0.2591 "
Ca max	0.2709 "
rNs min	0.0197 "
D3 max	4.5358 "
b min	0.1220 "
b max	0.1339 "
r0 max	0.0236 "
D4 max	5.1063 "
f	0.1110 "
Snap ring reference	R120
rs min	0.0591 "
r1s min	0.0591 "
Radial clearance class	C3
Mass (without HJ ring)	4.13 oz
Brand	NTN



Product performance	
Dynamic load, C	108 kN
Static load, C0	119 kN
Fatigue limit load, Cu	14.50 kN
Nlim (oil)	6,300 RPM
Nlim (grease)	5,400 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.07 Hz
Characteristic outer ring frequency, BPF0	6.72 Hz
Characteristic inner ring frequency, BPF1	9.28 Hz



Abutment dimensions

da min	2.8740 "
dc min	3.4252 "
Da max	4.4094 "
DbN min	5.1772 "
ra max	0.0591 "
rNa max	0.0197 "

Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$P_0 = Fr$$