

## PDF technical sheet NUP2205ET2X




### Single row cylindrical roller bearings

Single row cylindrical roller bearing, locating, separable, polyamide cage


#### Product definition

|                        |          |
|------------------------|----------|
| d                      | 0.9843 " |
| D                      | 2.0472 " |
| B                      | 0.7087 " |
| E                      | 1.8307 " |
| F                      | 1.2402 " |
| d1                     | 1.3583 " |
| rs min                 | 0.0394 " |
| r1s min                | 0.0236 " |
| Radial clearance class | CN       |
| Mass (without HJ ring) | 0.59 oz  |
| Brand                  | NTN      |



#### Product performance

|                                               |            |
|-----------------------------------------------|------------|
| Dynamic load, C                               | 35 kN      |
| Static load, C0                               | 34.50 kN   |
| Fatigue limit load, Cu                        | 4.20 kN    |
| Nlim (oil)                                    | 13,000 RPM |
| Nlim (grease)                                 | 11,000 RPM |
| Min operating temperature, Tmin               | -40 °C     |
| Max operating temperature, Tmax               | 248 °C     |
| Characteristic cage frequency, FTF            | 0.40 Hz    |
| Characteristic rolling element frequency, BSF | 5.01 Hz    |
| Characteristic outer ring frequency, BPF0     | 5.25 Hz    |
| Characteristic inner ring frequency, BPF1     | 7.75 Hz    |



#### Abutment dimensions

|        |          |
|--------|----------|
| da min | 1.1811 " |
| dc min | 1.4567 " |
| Da max | 1.8504 " |
| ra max | 0.0394 " |

#### Calculation factors

Equivalent dynamic radial load

$$P = F_r$$

Equivalent static radial load

$$P_0 = F_r$$