

PDF technical sheet


NUP2311EG1C4U




Single row cylindrical roller bearings

Single row cylindrical roller bearing, locating, separable, brass cage

Product definition	
d	2.1654 "
D	4.7244 "
B	1.6929 "
E	4.1929 "
F	2.7756 "
d1	3.0591 "
rs min	0.0787 "
r1s min	0.0787 "
Radial clearance class	C4
Mass (without HJ ring)	8.11 oz
Brand	NTN



Product performance	
Dynamic load, C	201 kN
Static load, C0	233 kN
Fatigue limit load, Cu	28.40 kN
Nlim (oil)	5,600 RPM
Nlim (grease)	4,700 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.40 Hz
Characteristic rolling element frequency, BSF	4.71 Hz
Characteristic outer ring frequency, BPF0	5.18 Hz
Characteristic inner ring frequency, BPF1	7.82 Hz



Abutment dimensions	
da min	2.5197 "
dc min	3.1496 "
Da max	4.3701 "
ra max	0.0787 "

Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$Po = Fr$$