


PDF technical sheet N228EMJ30




Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, brass cage

Product definition	
d	5.5118 "
D	9.8425 "
B	1.6535 "
E	8.8583 "
F	6.6535 "
d1	7.0630 "
rs min	0.1181 "
r1s min	0.1181 "
Radial clearance class	C3
Mass (without HJ ring)	33.47 oz
Brand	SNR



Product performance	
Dynamic load, C	397 kN
Static load, C0	522 kN
Fatigue limit load, Cu	51.90 kN
Nref	2,600 RPM
Nlim	4,100 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.89 Hz
Characteristic outer ring frequency, BPF0	8.15 Hz
Characteristic inner ring frequency, BPF1	10.85 Hz



Abutment dimensions	
da min	6.0236 "
Da max	9.3307 "
Db min	8.9764 "
Dc max	8.7795 "
ra max	0.0984 "
r1a max	0.0984 "

Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$P_0 = Fr$$