

## PDF technical sheet NJ2210EG15



### Single row cylindrical roller bearings

Single row cylindrical roller bearing, single direction for axial loads, separable, polyamide cage.

| Product definition     |          |
|------------------------|----------|
| d                      | 1.9685 " |
| D                      | 3.5433 " |
| B                      | 0.9055 " |
| E                      | 3.2087 " |
| F                      | 2.3425 " |
| d1                     | 2.5197 " |
| D1                     | 3.0827 " |
| rs min                 | 0.0433 " |
| r1s min                | 0.0433 " |
| Radial clearance class | CN       |
| Mass (without HJ ring) | 2.07 oz  |
| Brand                  | SNR      |



| Product performance                           |           |
|-----------------------------------------------|-----------|
| Dynamic load, C                               | 81.30 kN  |
| Static load, C0                               | 94.10 kN  |
| Fatigue limit load, Cu                        | 11.50 kN  |
| Nref                                          | 5,200 RPM |
| Nlim                                          | 9,200 RPM |
| Min operating temperature, Tmin               | -4 °C     |
| Max operating temperature, Tmax               | 248 °C    |
| Characteristic cage frequency, FTF            | 0.42 Hz   |
| Characteristic rolling element frequency, BSF | 6.25 Hz   |
| Characteristic outer ring frequency, BPF0     | 6.75 Hz   |
| Characteristic inner ring frequency, BPF1     | 9.25 Hz   |



| Abutment dimensions |          |
|---------------------|----------|
| da min              | 2.2244 " |
| da max              | 2.2835 " |
| db min              | 2.4409 " |
| dc min              | 2.6378 " |
| Da max              | 3.2874 " |
| ra max              | 0.0394 " |
| r1a max             | 0.0394 " |

### Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$P_0 = Fr$$