

PDF technical sheet NJ2320EMJ40




Single row cylindrical roller bearings

Single row cylindrical roller bearing, single direction for axial loads, separable, brass cage.

Product definition	
d	3.9370 "
D	8.4646 "
B	2.8740 "
E	7.5394 "
F	5.0197 "
d1	5.4882 "
D1	7.1654 "
rs min	0.1181 "
r1s min	0.1181 "
Radial clearance class	C4
Mass (without HJ ring)	47.62 oz
Brand	SNR



Product performance	
Dynamic load, C	579 kN
Static load, C0	732 kN
Fatigue limit load, Cu	77.60 kN
Nref	2,500 RPM
Nlim	5,000 RPM
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	248 °C
Characteristic cage frequency, FTF	0.40 Hz
Characteristic rolling element frequency, BSF	4.78 Hz
Characteristic outer ring frequency, BPF0	5.20 Hz
Characteristic inner ring frequency, BPF1	7.80 Hz



Abutment dimensions	
da min	4.4488 "
da max	4.9213 "
db min	5.1969 "
dc min	5.6299 "
Da max	7.9528 "
ra max	0.0984 "
r1a max	0.0984 "

Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$P_0 = Fr$$