


## PDF technical sheet NU2306EG15



### Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, polyamide cage

| Product definition     |          |
|------------------------|----------|
| d                      | 1.1811 " |
| D                      | 2.8346 " |
| B                      | 1.0630 " |
| E                      | 2.4606 " |
| F                      | 1.5945 " |
| D1                     | 2.3307 " |
| rs min                 | 0.0433 " |
| r1s min                | 0.0433 " |
| Radial clearance class | CN       |
| Mass (without HJ ring) | 1.87 oz  |
| Brand                  | SNR      |



| Product performance                           |            |
|-----------------------------------------------|------------|
| Dynamic load, C                               | 75.90 kN   |
| Static load, C0                               | 79.50 kN   |
| Fatigue limit load, Cu                        | 9.70 kN    |
| Nref                                          | 7,200 RPM  |
| Nlim                                          | 12,000 RPM |
| Min operating temperature, Tmin               | -4 °C      |
| Max operating temperature, Tmax               | 248 °C     |
| Characteristic cage frequency, FTF            | 0.39 Hz    |
| Characteristic rolling element frequency, BSF | 4.47 Hz    |
| Characteristic outer ring frequency, BPF0     | 4.72 Hz    |
| Characteristic inner ring frequency, BPF1     | 7.28 Hz    |



| Abutment dimensions |          |
|---------------------|----------|
| da min              | 1.4370 " |
| da max              | 1.5748 " |
| Da max              | 2.5787 " |
| ra max              | 0.0394 " |
| r1a max             | 0.0394 " |

### Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$P_0 = Fr$$